



	IP CAMERA IPC3614SB-ADF28KMC-I0 Tri-Guard - 4 Mpx 2.8 mm UNIVIEW	SWITCH POE GTX-A1-06-42-V2 4-PORT
		
	273.97 EUR 273.97 EUR	32.84 EUR 32.84 EUR
Standard	TCP/IP	...
Sensor	1/2.7 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
LAN ports	...	<ul style="list-style-type: none"> • 4 x RJ45 10/100 Base-T (4 x PoE (802.3af/at)), • 2 x RJ45 10/100 Base-T - Uplink
Management	...	—
LED diodes	...	Power, S - Extend, PoE, Link/Act
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	...
Lens	2.8 mm	...
Transmission speed	...	10 / 100 Mbps : 4 LAN & PoE ports + 2 Uplink ports
View angle	<ul style="list-style-type: none"> • 101 ° (manufacturer data) • 96 ° (our tests result) 	...
Maximal output power	...	30 W / port PoE 802.3af/at - 1 ... 4 ports
White light LED illuminator range	30 m	...
Maximal total power	...	60 W
Range of IR illumination	30 m	...
S/N ratio	> 56 dB	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Operation modes	...	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • S - Extend - Range : 250 m @ 10 Mbps
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Certificates	...	CE

Audio	<ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Audio transmission via network • Audio detection 	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-TX (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Operation temp	...	-10 °C ... 55 °C
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...

Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • Active deterrence function - Light and sound alarm • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • ROI - improve the quality of selected parts of image • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, people counting, crowd gathering estimation, face detection • Overvoltage protection : 4 kV 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 625 mA 	100 ... 265 V AC
Power consumption	≤ 7.5 W	...
Housing	Dome, Metal	Desktop, Metal
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.42 kg	0.49 kg
Dimensions	Ø 110 x 95 mm	145 x 100 x 32 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	...
Guarantee	3 years	2 years