




	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTI-AI70FRTD-V2 4.5 mm - 1080p	ELECTRIC CABLE DY-2.5-BN/750V
		
	59.60 EUR 59.60 EUR	0.39 EUR 0.39 EUR
Scanning system	Progressive	...
In section	...	100 m . Price for 1m when buying a whole roll
Inner conductor	...	2.5 mm ² - Cu wire
Optical zoom	—	...
Rated voltage	...	450 / 750 V
Outer coating	...	Ø 3.3 mm - PVC
Coating color	...	Brown
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS 1/5 " GC2145	...
Matrix size	2.1 Mpx 2 Mpx	...
Pixel pitch	1.75 µm	...
Lens	4.5 mm 2.4 mm	...
View angle	68 ° 70 °	...
Resolution	1920 x 1080 - 1080p 800 x 600 - 0.48 Mpx	...
Standard	TCP/IP	...
Range of IR illumination	5 m	...
White light LED illuminator range	5 m	...
Temperature measurement	✓	...
Temperature measurement range	35 °C ... 42 °C	...
Accuracy of temperature measurement	± 0.3 °C	...
Face recognition distance	0.5 m ... 1.5 m (max 30 000 faces in the database)	...
Temperature measurement distance	0.5 m ... 1.3 m optimal distance : 0.75 m	...

Internal memory	Support storage of 25 000 records	...
Video output	—	...
RS-485 interface	✓	...
Wiegand interface	✓	...
Memory card slot	—	...
Alarm inputs / outputs	0 / 2 (bolt control, signaling of exceeding the temperature)	...
Audio	Speaker built-in	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4, HTTP, HTTPS, TCP/IP	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	—	...
RS-485	✓	...
Default IP address	DHCP / 192.168.1.88	...
Default admin user / password	admin / 12345	...
Web browser access ports	7080	...
PC client access ports	7080	...
Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera and the result of temperature measurement - 1024 x 600 px • Wiegand 26 • Day/Night mode (color/b&w/auto) • RESET button • Relay output operating modes: access control or notification of an exception 	...
Power supply	12 V DC	...
Power consumption	≤ 12 W	...
Housing	Compact - Metal	...
Color	Silver	...
"Index of Protection"	IP66	...
Operation temp	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)	...
Weight	0.94 kg	...
Dimensions	305 x 112 x 59 mm	...
Montage hole diameter	33 mm	...
Length of the cable	64 cm	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	APTI	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00