



	ACCESS CONTROLLER MODULE MC16-PAC-ST-3 ROGER	ACCESS CONTROLLER WITH FACE RECOGNITION + READER ATLO-FR-601
		
	168269.23 HUF 168269.23 HUF	19134.62 HUF 19134.62 HUF
Number of served transitions	3 (two-way)	...
Number of supported readers	12	...
Face recognition distance	...	0.5 m ... 1 m (max 1000 faces in the database)
Number of users	unlimited (purchase of the appropriate license required)	...
RFID proximity reader built-in	...	Unique EM 125kHz - Number of supported proximity cards : 10 000
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Fingerprint reader built-in	...	Memory of 600 fingerprint patterns
Buffer memory	8 000 000 events buffer	...
Range of IR illumination	...	5 m
Number of access zones	6	...
White light LED illuminator range	...	—
Video output	...	—
Number of alarm zones	6	...
Wiegand interface	...	✓
RS-485 interface	...	—
Battery backup support	12 V / 7 Ah	...
Alarm inputs / outputs	...	0 / 1 - Relay output
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	...

Main features	...	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera • Identification modes : Face recognition, Fingerprint, Proximity identifier Unique EM 125kHz, Any combination of the above • Wiegand 26 • LEDs and buzzer • Buzzer for acoustic signaling of some system events
Main features	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	...
Power consumption	...	≤ 3.6 W (operation) ≤ 2.2 W (standby)
Housing	...	Aluminum + Tempered glass, Vandal-proof
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	12 V DC
Color	...	Silver + Black
"Index of Protection"	...	IP65
Operation temp	5 °C ... 40 °C	...
Operation temp	...	-40 °C ... 60 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Weight	0.14 kg	0.38 kg
Dimensions	175 x 72 x 30 mm	170 x 70 x 24 mm
Manufacturer / Brand	ROGER	ATLO
Guarantee	3 years	2 years