


	STYROFOAM PLUG FISCHER FID-90	IP CAMERA IPC-HFW2849S-S-IL-0360B WizSense - 8.3 Mpx 4K UHD 3.6 mm DAHUA	STEEL CABLE LS-5/100/PVC	ACCESS CONTROLLER MC16-PAC-ST-1-KIT ROGER
				
	1.28 EUR 1.28 EUR	304.61 EUR 304.61 EUR	1.00 EUR 1.00 EUR	353.42 EUR 353.42 EUR
Length	90 mm
Standard	...	TCP/IP
Diameter	Ø 25 mm
Number of served transitions	1 (two-way)
Sensor	...	1/2.7 " Progressive Scan CMOS
Thickness of the Styrofoam	≥ 90 mm
Number of supported readers	4
Matrix size	...	8.3 Mpx 4K UHD
Diameter of the screw	Ø 6 mm
In section	100 m . Price for 1m when buying a whole roll	...
Number of users	unlimited (purchase of the appropriate license required)
Material	Steel + PVC	...
External diameter	Ø 5 mm	...
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Inner diameter	Ø 4.5 mm	...
Buffer memory	8 000 000 events buffer
Tensile strength	1030 kg	...
Number of access zones	4
Number of alarm zones	4
Battery backup support	12 V / 20 Ah
Communication	<ul style="list-style-type: none"> Ethernet - RJ-45 socket RACS 5 v2 (Roger) RS-485 interface
Main features	<ul style="list-style-type: none"> Metal housing Integrated support in VISO ST software Functions in the VISO ST system: <ul style="list-style-type: none"> MSSQL database work in distributed systems multi-station work monitoring of transitions with video preview T&A event reporting maximum number of transitions in the system : 128
Resolution	...	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2880 x 1620 - 4.6 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Scanning system	...	Progressive
Lens	...	3.6 mm
Operation temp	5 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)
View angle	...	<ul style="list-style-type: none"> 87 ° (manufacturer data) 83 ° (our tests result)
Range of IR illumination	...	30 m
White light LED illuminator range	...	30 m
Min. illumination	...	0.002 Lux / F1.0 (color)
S/N ratio	...	> 56 dB

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Audio detection • Compliance with the AAC standard
Main stream frame rate	...	20 fps @ 8.3 Mpx 25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour
WEB Server	...	Built-in
Max. number of on-line users	...	20
ONVIF	...	21.12
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles video tampering
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA 	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Power consumption	...	<ul style="list-style-type: none"> • ≤ 5 W @ 12 V DC • ≤ 5.9 W @ PoE
Housing	...	Compact - Metal
Color	...	White + Black
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	0.012 kg	0.47 kg	...	3.9 kg
Dimensions	...	166 x 70 x 70 mm	...	405 x 365 x 120 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	...	DAHUA	...	ROGER
Guarantee	2 years	3 years	2 years	3 years


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00