



	IP CAMERA IPC2122LB-AF28WK-G-BLACK Wi-Fi - 1080p 2.8 mm UNIVIEW	IP CAMERA T2A-PV Wi-Fi, Smart Dual Light Active Deterrence - 1080p 2.8 mm DAHUA
		
	128.23 EUR 128.23 EUR	41.05 EUR 41.05 EUR
Standard	TCP/IP	IP
Matrix size	2.1 Mpx	...
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Sensor	1/2.9 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Lens	2.8 mm	2.8 mm
View angle	<ul style="list-style-type: none"> • 101 ° (manufacturer data) • 92 ° (our tests result) 	98 °
Range of IR illumination	30 m	30 m
S/N ratio	> 52 dB	...
White light LED illuminator range	...	30 m
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	H.265 / H.264 H.264B / H.264H
Alarm inputs / outputs	—	—
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network, • Audio detection 	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support
Main stream frame rate	25 fps @ 1080p	25 fps @ 1080p
Interface	...	<ul style="list-style-type: none"> • Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz, • 10/100 Base-T (RJ-45)
Network interface	<ul style="list-style-type: none"> • Wi-Fi - 2.4 GHz IEEE 802.11 b/g/n, • 10/100 Base-T (RJ-45) 	...
Intelligent image analysis	...	Human detection
Network protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, SNMP	...
WEB Server	Built-in	Built-in
Max. number of on-line users	32	...
ONVIF	✓	✓
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	DHCP or 192.168.1.13	192.168.1.108
Default admin user / password	admin / 123456	admin / - The administrator password should be set at the first start
Web browser access ports	80, 554	80, 37777
Mechanical protection class	...	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	37777
Mobile client access ports	80	37777
Port ONVIF	80	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	<ul style="list-style-type: none"> • Wi-Fi Module, Range : 130 m • D-WDR - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Vertical or horizontal image mirror • Privacy zones - max. 4 • Motion Detection - max. 4 zones • Intelligent image analysis : Human detection 	<ul style="list-style-type: none"> • Active deterrence function • Smart Dual Light • Built-in hybrid illuminator (LED - IR/white) • Day/night mode • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Motion Detection
Power supply	12 V DC / 340 mA	12 V DC / 1 A (power adapter included)
Power consumption	≤ 4 W	max. 6.9 W
Housing	Compact, Metal + Plastic	Dome - Plastic
Color	Black	White
"Index of Protection"	IP67	IP67
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.27 kg	0.34 kg
Dimensions	172 x 76 x 72 mm	Ø 110 x 102 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English
Manufacturer / Brand	UNIVIEW	DAHUA
Guarantee	3 years	3 years