




	CONVERTER HDMI-OFT-20IR	WIRELESS PIR DETECTOR ATLO-AC-AP96	CABLE USB-W-C/USB-W-1M/NYL-B 1.0 m
			
	140.66 GBP 140.66 GBP	7.65 GBP 7.65 GBP	1.53 GBP 1.53 GBP
Support	...	alarm control panel ATLO-AZ-WG13A-TUYA	...
Cable	USB-C plug / USB-A plug
Material	Nylon
Battery power supply	...	1 x 9V, type 6LR61 battery (included)	...
Length of the cable	1.0 m
Color	Black
Frequency range	...	433 MHz	...
USB standard	2.0
Radio communication range (at open area)	...	≥ 100 m	...
Recommended installation height	...	2.2 m	...
Outputs	1 pcs LC 1 pcs JACK IR transmitter 1 pcs HDMI
Detection angle / Detection range	...	110 ° / 12 m	...
Inputs	1 pcs HDMI 1 pcs LC 1 pcs JACK IR receiver
Current consumption	...	≤ 15 µA - Standby ≤ 25 mA - Alarm signaling	...
Cable diameter	~ 3.5 mm
Pet immunity	...	< 15 kg	...
Main features	...	<ul style="list-style-type: none"> • Code 1527 data encryption • Tamper detection - opening the enclosure • Temperature compensation 	<ul style="list-style-type: none"> • Fast data transmission, fast charging • Max. current : 1.5 A • Nylon braid - kink resistant • Very flexible • Solid workmanship
Supported HDMI input resolutions	480i @ 60Hz 480p @ 60Hz 576i @ 50Hz 576p @ 50Hz 720p @ 50/60Hz 1080i @ 50/60Hz 1080p @ 50/60Hz

Mobile phones support	...	Access by a cloud (P2P) • The Tuya Smart free application on Android • The Tuya Smart free application on iOS	...
Supported HDMI output resolutions	480p @ 60Hz 576p @ 50Hz 720p @ 50/60Hz 1080p @ 50/60Hz
Operation temp	...	-10 °C ... 50 °C	...
Optical wavelength	• 1310 nm • 1550 nm
Weight	...	0.1 kg	0.028 kg
Connector type	LC
Fiber optic type	SMF 0-40km
Receiver sensitivity	≤ -32 dBm
Output power	≥ -11 dBm
Attenuation	≤ 14 dB
Manufacturer / Brand	...	ATLO	...
IR frequency	38 kHz
Dimensions	138 x 79 x 25 mm	110 x 61 x 48 mm	...
Guarantee	2 years	2 years	2 years