






	ACCESS POINT RG-RAP6262 Wi-Fi 6 2.4 GHz, 5 GHz 574 Mbps + 2402 Mbps REYEE	ACCESS POINT 4G+ LTE +ROUTER RUT361 2.4 GHz 300 Mbps Teltonika	ACCESS POINT 4G LTE +ROUTER CUDY-LT500D 2.4 GHz, 5 GHz, 867 Mbps + 300 Mbps	MONITOR DESK MOUNT MC-717 MACLEAN	ANGULAR SPEAKER PLUG WG2/KAT
					
	494.06 CAD 494.06 CAD	293.30 CAD 293.30 CAD	99.29 CAD 99.29 CAD	55.89 CAD 55.89 CAD	0.35 CAD 0.35 CAD
Connector type	plug / screw terminals
Mounting standard	VESA 100 x 100, 75 x 75	...
Material	PET / Metal
Screen size range	13 " ... 27 "	...
Application	Speaker cable
Bearing capacity	8 kg	...
Color	Silver / Black	Black
Tilt adjustment	-35 ° ... 35 °	...
Horizontal rotation	180 °	...
Rotation in the plane of the screen	360 °	...
Frequency range	2.4 GHz, 5 GHz	2.4 GHz	<ul style="list-style-type: none"> • Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz
Antenna type	2x2 MU-MIMO, 2.4 GHz - 3 dBi / 5.0 GHz - 4 dBi, Integrated - 5 x Omnidirectional antenna	2x2 MIMO : 2 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)	<ul style="list-style-type: none"> • 2 x Omnidirectional antenna Wi-Fi, Integrated, 5 dBi, • 2 x Omnidirectional antenna 4G LTE, 5 dBi / SMA connector for connecting an external antenna
Standards	IEEE 802.11 a/b/g/n/ac/ax	IEEE 802.11 b/g/n, 4G+ Cat.6 LTE, 3G	IEEE 802.11 a/b/g/n/ac
Baud rates	2.4 GHz : max. 574 Mbps + 5 GHz : max. 2402 Mbps	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 300 / 42 Mbps (4G / 3G)	<ul style="list-style-type: none"> • Wi-Fi : 867 Mbps + 300 Mbps, • LTE : 150 Mbps / 50 Mbps
Network type	...	4G, 3G
LED indicators	...	Power, WAN, WLAN, LAN, LTE - 3G/4G, Signal indicator	Power, INTERNET, LTE, 4 x Ethernet
SIM socket	1 x nano SIM
DDNS	✓
Firmware update	✓
LAN ports	1 x 10/100/1000 Mbps 1 x 1000 Base-X port SFP	<ul style="list-style-type: none"> • 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN 	1 x 10/100 Mbps - Uplink / LAN 3 x 10/100 Mbps - LAN
Mobile phones support	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
LTE	...	✓
QSS	...	—
WDS	...	—
DHCP server	...	✓	✓

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default IP address	10.44.77.253
Transmitter power	≤ 32 dBm @ 2.4 GHz ≤ 34.7 dBm @ 5 GHz	≤ 17.51 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA	< 20 dBm
Housing	Outdoor, plastic (Weatherproof)
Overvoltage protection	4 kV lightning
Protections	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK	<ul style="list-style-type: none"> • WPA3-EAP • WPA3-SAE • WPA2-Enterprise - PEAP • WPA2-PSK • AES-CCMP • WEP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering 	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Power supply PoE	✓
Management interface	Web browser, Ruijie Cloud	Web browser, Teltonika RMS application, SMS	Web browser
Certificates	CE, RoHS
Power supply	<ul style="list-style-type: none"> • PoE (802.3at) • 12 V / 2 A (power adapter not included) 	<ul style="list-style-type: none"> • 12 V DC / 1.5 A (power adapter included) • 9 ... 30 V DC 	12 V DC / 1 A (power adapter included)
Power consumption	≤ 24 W	≤ 4.7 W
Operation temp	-30 °C ... 65 °C	-40 °C ... 75 °C
Permissible relative humidity	0 % ... 100 %	10 % ... 90 % (non-condensing)
Main features	<ul style="list-style-type: none"> • Access Point is managed through the web and the cloud (Ruijie Reyee application) • Mobile phones support • Number of users : 512 (max) • Multi-SSID (max. 8) • Enable/Disable Wireless Radio • WMM (Wi-Fi Multimedia) • Transmit power control • Support for Reyee Mesh technology • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • Load balance • Rate limit • Wireless Network Schedule • Wireless transmission statistics • Access control • MAC addresses filtering • Wireless isolation between clients • SSID to VLAN mapping • Remote management • RESET button • LED indication • Power supply PoE • Easy to install on any wall or pole (mounting kit included) 	<ul style="list-style-type: none"> • Support for IoT (Internet of Things) systems, • Ability to work as a Hotspot, • Support for VoIP technology, • Support for Mesh technology • SIM socket • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems 	<ul style="list-style-type: none"> • Built-in 4-port switch • WPS button • The WPS function allows to easy establish an encrypted connection • RESET button • VPN networks: OpenVPN, WireGuard, IPSec, PPTP, L2TP, Zerotier VPN • DNS - Cloudflare, NextDNS, Google • Dynamic DNS • SMS personal messaging • Guest Network - a separate and secure network for guests • Watchdog 4G function • Wireless Network Schedule • WMM (Wi-Fi Multimedia) • Static / dynamic routing • DHCP client/server support, address reservation • NAT network firewall, Port forwarding, UPnP, DMZ • Access control • Remote management • IPv6 compliance • 4G bands lock

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	IP68
Weight	2.67 kg (without mounting kit)	0.25 kg	0.316 kg	2.25 kg	0.002 kg
Dimensions	395 x 230 x 195 mm (without mounting kit)	100 x 93 x 30 mm	242 x 175 x 38 mm	117 x 246 x 468 mm	18.5 x 11 x 11 mm
Pole diameters range	Ø 70 ... Ø 140 mm
Manufacturer / Brand	RUIJIE / REYEE	Teltonika	CUDY	MACLEAN	...
Guarantee	3 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00