


	AHD, HD-CVI, HD-TVI CAMERA APTI- H50PC21-28W 2Mpx / 5Mpx 2.8 mm	SWITCH POE NSW2020-24T1GT1GC-POE-IN 24-PORT SFP UNIVIEW	SPEAKER MOUNT BRATECK-SB-24
			
	24.97 EUR 24.97 EUR	376.28 EUR 376.28 EUR	2.20 EUR 2.20 EUR
Standard	AHD, HD-CVI, HD-TVI
In package	2 pcs The price for package
Bearing capacity	3.5 kg
Sensor	1/3 " Progressive Scan CMOS
Distance from mounting surface	60 mm
Matrix size	5 Mpx
Tilt adjustment	± 20 °
LAN ports	...	<ul style="list-style-type: none"> • 24 x RJ45 (24 x PoE (802.3af/at)), • 1 x RJ45 - Uplink, • 1 x Combo: RJ45/SFP - Uplink 	...
Horizontal rotation	± 70 °
Management	...	—	...
LED diodes	...	G1/SFP1, G2, PoE Max, Power, Link/Act, PoE	...
Transmission speed	...	<ul style="list-style-type: none"> • 100 Mbps : 24 LAN & PoE ports, • 1000 Mbps : 2 LAN ports - Uplink, • 1000 Mbps : 1 Port SFP - Uplink 	...
Resolution	<ul style="list-style-type: none"> • 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps ; • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps
Maximal output power	...	30 W / port PoE 802.3af/at	...
Lens	2.8 mm
Maximal total power	...	370 W	...
MAC addresses table	...	16k	...

View angle	<ul style="list-style-type: none"> • 95 ° (manufacturer data) • 83 ° (our tests result)
Range of IR illumination	20 m
IR illuminator power adjustment	Automatic
Operation modes	...	<ul style="list-style-type: none"> • Default : 100 m, 100 Mbps • Extend : 250 m, 10 Mbps • VLAN - 1 ... 24 ports are isolated from each other and separately work with the G1, G2 ports 	...
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch
OSD menu	✓
Main features	...	<ul style="list-style-type: none"> • High priority ports : 1 ... 8 • Data Flow Control • Buffer optimization • Power supply PoE - wires : 4-5(+), 7-8(-) • Metal housing • Can be mounted in a Rack 19" cabinet 	...
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines
Certificates	...	CE, FCC	...
Power consumption	≤ 2.6 W
Housing	Compact - Plastic	Desktop, Metal	...
Color	White
"Index of Protection"	IP66
Power supply	12 V DC / 220 mA	100 ... 240 V AC, 50 / 60 Hz	...
Operation temp	-20 °C ... 60 °C
Operation temp	...	0 °C ... 40 °C	...
Weight	0.19 kg	2.89 kg	0.06 kg
Dimensions	174 x 70 x 68 mm	440 x 245 x 44 mm, RACK 19", 1U	87 x 47 x 60 mm
Supported languages	Polish, English

Manufacturer / Brand	APTI	UNIVIEW	BRATECK
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00