



	POWER GENERATOR FH-8000TR 3500 W / 7000 VA Honda GX 390 FOGO	SEPARATOR WITH VIDEO BALUN D-SEP/HD-4/TR
		
	1965.44 EUR 1965.44 EUR	24.22 EUR 24.22 EUR
Nominal power	3500 W - Single-phase installation / 7000 VA @ 0.8 (cosφ) - Three-phase installation	...
Output voltage	<ul style="list-style-type: none"> • 230 V AC, • 400 V AC 	...
Standard	...	<ul style="list-style-type: none"> • AHD - 8 Mpx, 4K UHD • HD-CVI - 8 Mpx, 4K UHD • HD-TVI - 8 Mpx 4K UHD • CVBS - PAL / NTSC
Number of outlets	<ul style="list-style-type: none"> • 1 pcs - single-phase 16 A (max), • 1 pcs - three-phase 16 A (max) 	...
Built-in voltmeter	—	...
Output frequency	50 Hz	...
Voltage stabilization	AVR	...
12V DC output	—	...
Engine capacity	389 cm ³	...
Video transmission range	...	<ul style="list-style-type: none"> • 250 m @ 720p - UTP cat. 5e • 150 m @ 1080p - UTP cat. 5e • 400 m @ CVBS - PAL / NTSC - UTP cat. 5e
Device type	...	Passive
Number of channels	...	4 pcs Video
Number of inputs	...	4 pcs cable terminals
Number of outputs	...	4 pcs BNC socket
Engine type	Honda GX 390 1 cylinder, 4 stroke, gasoline, air cooled	...
Input impedance	...	100 Ω
Starting the engine	Manual	...
Output impedance	...	75 Ω
Noise level during operation	96 dB	...
Opto-isolation between inputs and outputs	...	50 V DC

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Galvanic separation between individual channels	...	> 2000 V
Average fuel consumption	2.7 l/h - 75 % power	...
Fuel tank capacity	45 l	...
Fuel gauge	✓	...
Main features	<ul style="list-style-type: none"> • Working time with a full fuel tank : 16.7 h - 75 % power, • Low oil level indicator light, • Overload protection, • Silencer with exhaust gas hose connection 	...
Color	White + Black	...
Attenuation	...	<ul style="list-style-type: none"> • 4.43 MHz @ 0.34 dB • 11 MHz @ 0.49 dB • 21 MHz @ 0.71 dB • 38 MHz @ 1.00 dB • 42 MHz @ 1.08 dB • 67.5 MHz @ 1.70 dB <p>The attenuation applies to two devices connected to each other</p>
Bandwidth	...	200 MHz
CMRR (dB @ 5MHz)	...	50 dB
Inputs protection	...	<p>ESD, IEC 61000-4-2, ±30kV contact, ±30kV air</p> <p>EFT, IEC 61000-4-4, 40A (5/50ns)</p> <p>Lightning, IEC 61000-4-5, 30A (t_p=8/20µs)</p>
Power supply	...	—
Operation temp	...	-20 °C ... 55 °C
Weight	86.1 kg	0.09 kg
Dimensions	790 x 580 x 650 mm	103 x 75 x 30 mm
Manufacturer / Brand	FOGO	DELTA
Guarantee	3 years - The condition is to conduct paid service every year - a warranty inspection at authorized Honda or FOGO service stations, otherwise 12 months	3 years