

	<a href="#">CABLE TIE HOLDER PS-4-19X19/W</a>	<a href="#">IP CAMERA IPC-HFW1230DS-SAW-0280B Wi-Fi - 1080p 2.8 mm DAHUA</a>
		
	0.09 EUR 0.09 EUR	139.42 EUR 139.42 EUR
Holes dimensions	3.5 x 1.5 mm	...
Standard	...	TCP/IP
Montage hole diameter	Ø 5 mm	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx
Assembly	<ul style="list-style-type: none"> <li>• The bottom layer is equipped with a Scotch tape,</li> <li>• Mounting with screws</li> </ul>	...
Resolution	...	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> <li>• 100 ° (manufacturer data)</li> <li>• 95 ° (our tests result)</li> </ul>
Range of IR illumination	...	30 m
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio detection</li> <li>• Audio transmission via network</li> </ul>
Main stream frame rate	...	25 fps @ 1080p
Network interface	...	<ul style="list-style-type: none"> <li>• Wi-Fi - 2.4 GHz IEEE 802.11 b/g/n,</li> <li>• 10/100 Base-T (RJ-45)</li> </ul>
Network protocols	...	IPv4, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, DHCP, DNS, NTP, Multicast
WEB Server	...	Built-in
ONVIF	...	20.06
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>
Default IP address	...	DHCP
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80

RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> <li>• Wi-Fi Module, Range : 80 m (open area) ; Antenna - SMA socket</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - configurable Back Light Compensation</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Mirror - Mirror image</li> <li>• Motion Detection - max. 4 zones - Human detection</li> </ul>
Power supply	...	12 V DC / 350 mA (power adapter included)
Power consumption	...	≤ 4.1 W
Housing	...	Compact - Metal
Color	White	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	...	0.47 kg
Dimensions	19 x 19 x 5.5 mm	166 x 70 x 129 mm
Supported languages	...	English, Spanish, Russian
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00