




	WIRELESS DOORBELL WITH PIR DETECTOR GB-212 GreenBlue	BATTERY-FREE WIRELESS DOORBELL BUTTON ATLO-DB-2/TX	VIDEO SEPARATOR SV-1000P STANDARD: PAL
			
	95.25 PLN 95.25 PLN	16.72 PLN 16.72 PLN	141.29 PLN 141.29 PLN
Support	...	ATLO-DB-2/RX	...
Signaling mode	Optical - sound signaling	LED indication	...
Number of ring-tones	58
Standard	CVBS - PAL / NTSC
Number of inputs	1 pcs BNC
Number of outputs	1 pcs BNC
Volume adjustment	4 volume levels, 25 ... 110 dB
Input impedance	75 Ω
Operation range	max. 150 m in open area	max. 150 m in open area	...
Output impedance	75 Ω
Frequency band	433.92 MHz	433 MHz	...
"Index of Protection"	...	IP44	...
Galvanic (optical) isolation between signal inputs and outputs	1000 V peak
Opto-isolation between power and signal inputs / outputs	1000 V peak
Gain adjustment	-5 dB ... +5 dB
Bandwidth	9 MHz / 1 Vpp
Transmission error	0.75 % (f=3.58MHz, Vin=1Vpp)
Assembly	To the wall
Power supply	<ul style="list-style-type: none"> • 230 V AC - Wireless doorbell, • Battery 3 V CR2450 (included) - Wireless detector 	Electromagnetic transducer	12 V DC / 80 mA

Main features	<ul style="list-style-type: none"> • The doorbell (receiver) can work with a maximum of 8 motion detectors (transmitters) • Detector range : 4 m, 110 ° • Rotation angle : 360 ° (with bracket) • Low battery level alarm • Simple and quick device installation • For indoor use
Operation temp	-10 °C ... 55 °C
Weight	<ul style="list-style-type: none"> • 0.076 kg - Wireless doorbell • 0.024 kg - Wireless detector 	0.04 kg - Doorbell button	0.095 kg
Dimensions	<ul style="list-style-type: none"> • 81 x 81 x 70 mm - Wireless doorbell • 39 x 32 x 30 mm - Wireless detector (with bracket) 	75 x 40 x 20 mm	61 x 120 x 30 mm
Manufacturer / Brand	GreenBlue	...	DELTA
Guarantee	2 years	2 years	3 years