

| | POE POWER ADAPTER SPT-1/IP 15.4 W | OVERVOLTAGE LIMITER LE-412223 THREE-PHASE 2 TYPE LEGRAND | IP CAMERA IPC3614SB-ADF28KM-I0 - 4 Mpx 2.8 mm UNIVIEW |
|--|---|---|--|
| |  |  |  |
| | 576.66 CZK 576.66 CZK | 2103.54 CZK 2103.54 CZK | 7025.05 CZK 7025.05 CZK |
| Standard | ... | ... | TCP/IP |
| Standards | IEEE 802.3af | ... | ... |
| Sensor | ... | ... | 1/3 " Progressive Scan CMOS |
| Device type | ... | Overvoltage limiter, Three-phase | ... |
| Matrix size | ... | ... | 4 Mpx |
| Input voltage | 100 V ... 240 V AC | ... | ... |
| Scanning system | ... | ... | Progressive |
| Rated voltage | ... | 230 / 400 V AC, 50 / 60 Hz | ... |
| Output voltage | 48 ... 56 V DC | ... | ... |
| Number of inputs | 1 | ... | ... |
| Connector | 2 x RJ-45 socket | ... | ... |
| Maximal voltage | ... | 320 V AC, 50 / 60 Hz | ... |
| LED indicators | Power connection, PoE | ... | ... |
| Output power | 15.4 W | ... | ... |
| Class | ... | 2 type (Class C) | ... |
| Supported data rates | 10 / 100 Mbps | ... | ... |
| Protections | — | ... | ... |
| Protection level Up L/PE, N/PE | ... | 1.2 kV @ 8/20 μs (T2) | ... |
| Nominal discharge current (L/PE, N/PE) | ... | 5 kA @ 8/20 μs (T2) | ... |
| Resolution | ... | ... | 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p |
| Maximum stroke current (L/N, L/PE, N/PE) | ... | 20 kA @ 8/20 μs (T2) | ... |
| Lens | ... | ... | 2.8 mm |
| Operation temp. / Relative humidity | 0 °C ... 40 °C / 5 % ... 90 % | ... | ... |
| Operation state indication | ... | ✓ | ... |
| Connectors type | ... | screw terminals | ... |
| View angle | ... | ... | • 101 ° (manufacturer data) • 97 ° (our tests result) |
| Range of IR illumination | ... | ... | 30 m |
| S/N ratio | ... | ... | > 56 dB |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | |
|-------------------------------|-----|-----|---|
| Width in 17.5 mm modules | ... | 4 | ... |
| RS-485 interface | ... | ... | — |
| Memory card slot | ... | ... | Micro SD memory cards up to 256GB support (possible local recording) |
| Image compression method | ... | ... | Ultra 265 / H.265 / H.264 / MJPEG |
| Alarm inputs / outputs | ... | ... | — |
| Audio | ... | ... | <ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection |
| Main stream frame rate | ... | ... | 25 fps @ 4 Mpx |
| Network interface | ... | ... | 10/100 Base-T (RJ-45) |
| Network protocols | ... | ... | IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS, SSL / TLS, SSH |
| WEB Server | ... | ... | Built-in |
| Max. number of on-line users | ... | ... | 32 |
| ONVIF | ... | ... | ✓ |
| Mobile phones support | ... | ... | Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView |
| Default IP address | ... | ... | DHCP or 192.168.1.13 |
| Default admin user / password | ... | ... | admin / 123456 |
| Web browser access ports | ... | ... | 80, 554 |
| PC client access ports | ... | ... | Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation |
| Mobile client access ports | ... | ... | 80 |
| Port ONVIF | ... | ... | 80 |
| RTSP URL | ... | ... | rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream |



| | | | |
|-----------------------|------------------|-----------------------------------|---|
| Main features | ... | ... | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Image rotation and mirror • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, face detection, people counting, crowd gathering estimation |
| Power supply | ... | ... | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 330 mA |
| Power consumption | ... | ... | ≤ 4 W |
| Housing | Plastic | Plastic, DIN, TS-35 rail mounting | Dome, Metal |
| Color | ... | ... | White |
| "Index of Protection" | ... | ... | IP67 |
| Vandal-proof | ... | ... | — |
| Operation temp | ... | ... | -30 °C ... 60 °C |
| Weight | 0.166 kg | 0.334 kg | 0.44 kg |
| Dimensions | 145 x 65 x 43 mm | 71 x 83 x 70 mm | Ø 111 x 94 mm |
| Supported languages | ... | ... | Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian |
| Manufacturer / Brand | ... | LEGRAND | UNIVIEW |
| Guarantee | 2 years | 2 years | 3 years |

