



	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1500TRQ-0280B-S2 - 5 Mpx 2.8 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE76H0T-ITMF(2.8mm)(C) - 5 Mpx Hikvision
		
	651.27 SEK 651.27 SEK	779.29 SEK 779.29 SEK
Standard	HD-CVI, HD-TVI, AHD, CVBS	AHD / HD-CVI / HD-TVI / CVBS
Sensor	1/2.7 " Progressive Scan CMOS	Progressive Scan CMOS
Matrix size	5 Mpx	5 Mpx
Resolution	2880 x 1620 - 5 Mpx, HD-CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p, HD-CVI only 960 x 576 - 960H, PAL	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI • 1920 x 1080 - 1080p @ HD-TVI • 960 x 576 - 960H @ PAL
Range of IR illumination	25 m	30 m
IR illuminator power adjustment	Automatic	Automatic
Lens	2.8 mm	2.8 mm
View angle	<ul style="list-style-type: none"> • 111 ° (manufacturer data) • 105 ° (our tests result) 	<ul style="list-style-type: none"> • 85 ° (manufacturer data) • 82 ° (our tests result)
IR illuminator support	...	ICR - Movable InfraRed filter
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	—	...

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Day/night mode • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • Privacy zones • Mirror - Mirror image • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	OSD menu available via DAHUA recorder	OSD menu available via recorder
Power supply	12 V DC / 250 mA	12 V DC / 340 mA
Power consumption	≤ 3 W	≤ 4.3 W
Housing	Dome, Plastic	Dome, Metal
Color	White	White
"Index of Protection"	IP50	IP67
Vandal-proof	—	—
Operation temp	-40 °C ... 50 °C	-40 °C ... 60 °C
Weight	0.16 kg	0.29 kg
Dimensions	Ø 97 x 93 mm	91 x 83 x 68 mm
Manufacturer / Brand	DAHUA	Hikvision
SAP Code	...	300613623
Guarantee	3 years	3 years