



| | | |
|----------------------------|--|--|
| | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR BCS-L-XVR0801(6) 8 CHANNELS BCS Line | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR XVR5104HE-I3 4 CHANNELS DAHUA |
| |  |  |
| | 223.40 EUR 223.40 EUR | 230.32 EUR 230.32 EUR |
| Standard | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP |
| Video inputs | 8 pcs BNC | 4 pcs BNC |
| Video outputs | 1 pcs HDMI 1 pcs VGA | 1 pcs HDMI 1 pcs VGA |
| Audio inputs | 1 pcs CINCH | 4 pcs - CINCH 4 - Audio support via coaxial cable, HD-CVI only |
| Audio outputs | 1 pcs CINCH | 1 pcs CINCH |
| Image compression method | AI Coding / H.265+ / H.265 / H.264+ / H.264 | AI Coding / H.265+ / H.265 / H.264+ / H.264 |
| Image records resolutions | <ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 5 Mpx - 2560 x 1944 px 1,2,3,4 CH only , 5M-N - 1296 x 1440 px , 4M-N - 1280 x 1440 px , 1080p - 1920 x 1080 px , 1080N - 960 x 1080 px , 720p - 1280 x 720 px , • CVBS : 960H - 960 x 576 px • IP : max. 6 Mpx - 3072 x 2048 px | <ul style="list-style-type: none"> AHD / HD-CVI / HD-TVI : 5M-N - 1296 x 1440 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , CVBS : 960H - 960 x 576 IP : max. 6 Mpx - 3072 x 2048 |
| Recording speed adjustment | <ul style="list-style-type: none"> 6 Mpx IP @ 1 ... 25 fps 5 Mpx @ 1 ... 6 fps 1,2,3,4 CH only 5M-N @ 1 ... 12 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel | <ul style="list-style-type: none"> 6 Mpx IP @ 1 ... 25 fps 5M-N @ 1 ... 10 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel |
| Operation modes | 8 x AHD / HD-CVI / HD-TVI / CVBS / IP + 4 IP | 4 x AHD / HD-CVI / HD-TVI / CVBS / IP + 2 x IP |

| | | |
|------------------------------------|---|---|
| Recording modes | Manual, Motion Detection, Schedule | Manual, Sensor, Motion detection, Schedule |
| Supported hard drives | 1 x 16 TB SATA | 1 x 6 TB SATA |
| External storage devices backup | Save single frames and whole records from DVR drive to the USB drive | Save single frames and whole records from DVR drive to the USB drive |
| Searching and playback the records | Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) 1/4/9 channel synchronous playback | Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) Intelligent face search AI - simultaneous search in the archive of face recordings based on max 8 photos taking into account the similarity threshold (for each photo separately) 1/4 channel synchronous playback |
| Network interface | 1 x RJ-45 - 10/100 Base-TX | ... |
| Network functions | Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters , Web-Server built-in - 128 on-line users , ONVIF | Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users |
| Mobile phones support | Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager | Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
| Serial ports | RS-485 | ... |
| Alarm inputs / outputs | — | 8 / 3 |

| | | |
|---------------------------------|---|---|
| PTZ control | IP Speed Dome Cameras RS-485 - PELCO-D/P and others | IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P |
| Motion Detection | Split the screen into zones : 22 x 18 motion zones | Split the screen into zones : 22 x 18 motion zones |
| Intelligent image analysis | ✓ | ... |
| USB | 2 x USB 2.0 | 2 pcs USB 2.0 |
| Main features | <ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles • Smart motion detection (with recognizing people and vehicles) • face detection - supports 6 types of facial attributes extraction • Face recognition and analysis in real time (up to 8 photos per second) • Support for up to 10 face databases, including 10 000 face images • Cooperation with POS (Point of Sale) terminals • SMD PLUS - searching for an object classified as: human, motor vehicle • Privacy zones - max. 4 | <ul style="list-style-type: none"> • Cooperation with Dahua devices working in the concept of the Internet of Things (IoT), • POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window, • SMD PLUS - searching for an object classified as: human, motor vehicle • Coax Audio/Alarm support, • Intelligent image analysis : crossing the line (tripwire), intrusion, classification of people and vehicles • advanced face recognition and search functions • Support for up to 10 face databases, including 10 000 face images • Detection of faces not included in the device database • Searching for faces in recordings based on max 8 selected photos with the ability to independently set the similarity threshold for each photo |
| Mouse support | ✓ | ✓ |
| IR remote controller in the set | — | — |
| Power supply | 12 V DC / 2 A (power adapter included) | 12 V DC / 1.5 A (power adapter included) |
| Power consumption | max. 7 W (without HDD) | ... |
| Color | Black | Black |
| Weight | 0.9 kg | 1.18 kg |
| Dimensions | 260 x 235 x 47 mm | 325 x 257 x 55 mm |

| | | |
|----------------------|-----------------|---|
| Supported languages | Polish, English | Polish, English, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian |
| Country of origin | ... | China |
| Manufacturer / Brand | BCS Line | DAHUA |
| Guarantee | 3 years | 3 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00