



	<a href="#">ACCESS CONTROLLER PR311SE-BK ROGER</a>	<a href="#">ACCESS POINT 4G LTE +ROUTER TL-MR100 2.4 GHz 300 Mbps TP-LINK</a>
		
	107.29 EUR 107.29 EUR	61.69 EUR 61.69 EUR
Frequency range	...	2.4 GHz
Cards support	Unique EM 125kHz	...
Reading distance of prox-keys	max. 15 cm	...
Keyboard built-in	—	...
Communication	<ul style="list-style-type: none"> <li>• RS-485</li> <li>• RACS (Roger)</li> </ul>	...
Selected features of the standalone mode	<ul style="list-style-type: none"> <li>• 1000 indexed users</li> <li>• Operation with XM-2 I/O extension module (Full Standalone Mode)</li> </ul>	...
Antenna type	...	WiFi embedded , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna
Standards	...	IEEE 802.11 b/g/n
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps
Average current consumption	50 mA	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 1 x 10/100 Mbps - LAN/WAN</li> <li>• 1 x 10/100 Mbps - LAN</li> </ul>
Receiver sensitivity	...	<ul style="list-style-type: none"> <li>• 11g 54M : -74 dBm</li> <li>• 11n HT20 : -71 dBm</li> <li>• 11n HT40 : -68 dBm</li> </ul>
Transmitter power	...	< 20 dBm
LED indicators	...	Power, WAN, WLAN, LAN, GSM
Network type	...	<ul style="list-style-type: none"> <li>• 4G : FDD-LTE B1/B3/B5/B7/B8/B20 - 2100 / 1800 / 850 / 2600 / 900 / 800 MHz</li> <li>• 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz</li> <li>• 3G : HSPA/UMTS B1/B5/B8 - 2100 / 850 / 900 MHz</li> </ul>

LTE	...	✓
QSS	...	—
WDS	...	—
DDNS	...	<ul style="list-style-type: none"> <li>• DynDNS</li> <li>• No-IP</li> </ul>
DHCP server	...	✓
Firmware update	...	✓
Protections	...	<ul style="list-style-type: none"> <li>• WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK</li> <li>• SPI network firewall</li> <li>• IP-MAC Binding</li> </ul>
Management interface	...	Web browser
Operation modes	...	<ul style="list-style-type: none"> <li>• Router,</li> <li>• Router 4G LTE</li> </ul>
Main features	<ul style="list-style-type: none"> <li>• The ability to add additional reader (bilateral way door control),</li> <li>• 3 programmable input lines NO/NC,</li> <li>• 2 programmable transistor outputs 1A,</li> <li>• One programmable relay output 1.5A/30V,</li> <li>• Door modes (Normal, Locked, Unlocked and Conditionally Unlocked),</li> <li>• Any topology of communication bus,</li> <li>• "Guest" type additional users support defined individually on each controller,</li> <li>• Integration with an alarm system via in/out line ,</li> </ul>	<ul style="list-style-type: none"> <li>• Number of users - max. 32</li> <li>• SIM socket - The nanoSIM cards support</li> <li>• WPS/RESET button</li> <li>• Enable/disable wireless network</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• Wireless Network Schedule</li> <li>• Wireless transmission statistics</li> <li>• The failover function enabling automatic switching between 4G/WAN interface in the case of an Internet network connection loss</li> <li>• Static / dynamic routing</li> <li>• PPTP</li> <li>• L2TP</li> <li>• Remote management</li> <li>• DHCP client list</li> <li>• Port forwarding : UPnP, DMZ</li> <li>• Guest Network - a separate and secure network for guests</li> </ul>
Power supply	10 ... 15 V DC	9 V DC / 0.85 A (power adapter included)
Operation temp	-25 °C ... 60 °C	0 °C ... 40 °C
Permissible relative humidity	10 ... 95 % (non-condensing)	10 % ... 90 % (non-condensing)
Weight	0.18 kg	0.184 kg

Dimensions	152.5 x 46 x 23 mm (Standard housing stand) 152.5 x 46 x 35 mm (Thicker housing stand)	155 x 114 x 34 mm
Manufacturer / Brand	ROGER	TP-LINK
Guarantee	3 years	3 years