





	<a href="#">SET OF UTP / COAXIAL CONVERTERS FOR LAN+POE TRANSMISSION XCOAX4-SET 2 PCS SET ATTE</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-KL22-22F</a>	<a href="#">MONITORS DESK MOUNT MC-691 MACLEAN</a>	<a href="#">POWER CORD CABLE CEE-716/IEC-C7-3M 3 m</a>
				
	1322.99 NOK 1322.99 NOK	103.22 NOK 103.22 NOK	709.90 NOK 709.90 NOK	26.15 NOK 26.15 NOK
Cable	...	...	...	IEC320 C7 socket / CEE-716 plug
Length of the cable	...	...	...	3 m
Connectors	<ul style="list-style-type: none"> <li>• 1 pcs RJ45</li> <li>• 1 pcs cable terminal</li> <li>• 1 pcs BNC</li> </ul>	...	...	...
Voltage	...	...	...	max. 250 V
LAN ports	1 pcs RJ45 100 Mbps	...	...	...
Mounting standard	...	VESA : 50, 75, 100, 200 x 100, 200	VESA 75, VESA 100	...
Screen size range	...	23 " ... 42 "	13 " ... 27 "	...
Bearing capacity	...	35 kg	8 kg	...
Distance from mounting surface	...	19.5 mm	...	...
Color	...	Black	Black	...
Mount tube diameter	...	...	Ø 35 mm	...
Tilt adjustment	...	—	-45 ° ... 45 °	...
Horizontal rotation	...	—	180 °	...
Rotation in the plane of the screen	...	—	360 °	...
LAN+PoE port configuration description	<ul style="list-style-type: none"> <li>• xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+"-": 3, 6 pins) or ("+"-": 4, 5 pins; "+"-": 7, 8 pins)</li> <li>• xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W</li> </ul>	...	...	...
Transmission range	< 1000 m @ Coaxial cable < 100 m @ xCOAX4-SW - Switch PoE < 100 m @ xCOAX4-CAM - IP Camera	...	...	...
LED indicators	<ul style="list-style-type: none"> <li>• PoE</li> <li>• LAN</li> <li>• Link</li> <li>• 10Mb</li> </ul>	...	...	...

Protections	<ul style="list-style-type: none"> <li>• Overvoltage - LAN, BNC</li> <li>• Short-circuit - xCOAX4-SW</li> </ul>	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> <li>• Watchdog function - Coaxial cable</li> </ul>	...	...	<ul style="list-style-type: none"> <li>• Solid workmanship</li> <li>• 2 x 0.75 mm<sup>2</sup></li> </ul>
Power supply	xCOAX4-SW : <ul style="list-style-type: none"> <li>• 10 ... 58 V DC - cable terminal</li> <li>• PoE 802.3af/at / PASSIVE</li> <li>• The output PoE voltage is equal to the input voltage</li> </ul>	...	...	...
Power consumption	1.35 W (total)	...	...	...
Housing	Plastic (PC)	...	...	...
"Index of Protection"	IP20	...	...	...
Operation temp	-25 °C ... 65 °C	...	...	...
Weight	0.033 kg (single element)	0.422 kg	6 kg	0.11 kg
Dimensions	<ul style="list-style-type: none"> <li>• 73 x 52 x 20 mm - xCOAX4-SW</li> <li>• 73 x 52 x 20 mm - xCOAX4-CAM</li> </ul>	265 x 222 x 19.5 mm	1330 x 550 x 83 mm	...
Manufacturer / Brand	ATTE	BRATECK	MACLEAN	...
Guarantee	3 years	2 years	2 years	2 years

