





	MODULAR PLUG RJ45/L6*P100	EXPANSION PLUG KW-8/5X50 KLIMAS	VIDEO SEPARATOR D- SEP/HD	GSM ADAPTER CABLE SMA-G/TS9-0.2M-V2
				
	102.62 NOK 102.62 NOK	1.38 NOK 1.38 NOK	85.70 NOK 85.70 NOK	41.52 NOK 41.52 NOK
Cable	SMA socket / TS9
Length of the cable	0.2 m
In package	100 pcs The price for package
Drilling diameter	...	8 mm
Expansion plug length	...	50 mm
Connector type	RJ-45 - Plug, 8 pin
Attachment of connector elements	Crimping
Wire mounting	Clamping on each wire with 3-pin edge
Screw dimensions	...	Ø 5 x 50 mm, PZ-2
Application	Twisted-pair cable	HUAWEI E938 NOVATEL SIERRA ZTE AnyData
Material	PET	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized
Standard	<ul style="list-style-type: none"> • AHD - 8 Mpx, 4K UHD • HD-CVI - 8 Mpx, 4K UHD • HD-TVI - 8 Mpx 4K UHD • CVBS - PAL / NTSC 	...
Example of application	UTP cat. 6
Application	...	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick
Device type	Passive	...
Manufacturer / Brand	...	KLIMAS
Number of inputs	1 pcs BNC socket	...
Main features	<ul style="list-style-type: none"> • Very easy and quick assembly • To crimp use the crimping tool 	Very easy and quick assembly
Number of outputs	1 pcs BNC plug	...
Input impedance	75 Ω	...
Output impedance	75 Ω	...
Opto-isolation between inputs and outputs	25 V DC	...

Attenuation	<ul style="list-style-type: none"> • 4.43 MHz @ 0.34 dB • 11 MHz @ 0.42 dB • 21 MHz @ 0.59 dB • 38 MHz @ 0.91 dB • 42 MHz @ 0.91 dB • 67.5 MHz @ 1.01 dB 	...
Bandwidth	200 MHz	...
Power supply	—	...
Operation temp	-20 °C ... 55 °C	...
Weight	0.03 kg	...
Dimensions	49 x 20 x 17 mm	...
Guarantee	...	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00