





	<a href="#">SWITCH EXPERT- POE-1616/2M 18-PORT</a>	<a href="#">COAXIAL CABLE TRISSET-113/500</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-LCD-501N</a>	<a href="#">POWER METER WITH LCD DISPLAY UT-230B-EU UNI-T</a>
				
	10651.29 CZK 10651.29 CZK	14.98 CZK 14.98 CZK	91.00 CZK 91.00 CZK	691.37 CZK 691.37 CZK
LAN ports	• 16 x RJ45 ( 16 PoE ) • 2 x Uplink ( port SFP or RJ45 )	...	...	...
Device type	...	...	...	Power meter with LCD display
Power measurement	...	...	...	0.1 ... 3680 W
Mounting standard	...	...	VESA 75, 100	...
Screen size range	...	...	max. 32 "	...
In section	...	<b>500 m . Price for 1m when buying a whole roll</b>	...	...
AC voltage measurement	...	...	...	100 ... 260 V
Bearing capacity	...	...	30 kg	...
Coaxial cable	...	TRISSET	...	...
Maximal current	...	...	...	16 A
Distance from mounting surface	...	...	88 mm from wall	...
Maximal load	...	...	...	3680 W
Color	...	...	Black	...
Inner conductor	...	Ø 1.13 mm Cu Wire	...	...
Range of displayed power	...	...	...	0.0 ... 9999 W
Tilt adjustment	...	...	-15 ° ... 15 °	...
Dielectric	...	Ø 4.8 mm (physical foam)	...	...
Shield	...	Foil - Al/PET/Al	...	...
Range of displayed voltage	...	...	...	0.0 ... 9999 V
Horizontal rotation	...	...	-24 ° ... 24 °	...
Braid	...	81 % Al wire	...	...
Rotation in the plane of the screen	...	...	—	...
Outer coating	...	Ø 6.8 mm PVC	...	...
Range of displayed cumulative electricity	...	...	...	0.000 ... 9999 kWh
Coating color	...	White	...	...
Minimal bend radius	...	30 mm	...	...
Cumulative cost of electricity	...	...	...	0.00 ... \$ 9999
Impedance	...	75 Ω ± 3	...	...
Capacity	...	52 pF/m ± 2	...	...
Resistance of the inner conductor for DC current	...	16.85 Ω/km	...	...
Dielectric resistance	...	2000 MΩ/km	...	...
Screening efficiency	...	≥ 90 dB @100-900 MHz	...	...
Shortening wave coefficient	...	84 %	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Transmission speed	<ul style="list-style-type: none"> <li>• Ethernet - 10 Mbps Half Duplex, 20 Mbps Full Duplex</li> <li>• Fast Ethernet - 100 Mbps Half Duplex, 200 Mbps Full Duplex</li> <li>• Gigabit Ethernet - 2000 Mbps Full Duplex ( Uplink )</li> </ul>	...	...	...
Housing	...	...	...	Plastic
Security class	...	...	...	IP20
Maximal output power	15.4 W / port PoE	...	...	...
Maximal total power	247 W	...	...	...
Socket type	...	...	...	F type (Schuko)
Transmission method	Store and Forward	...	...	...
MAC addresses table	1k / device	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Configuration possibility from PC</li> <li>• Auto update of MAC addresses table</li> </ul>	<ul style="list-style-type: none"> <li>• low attenuation</li> <li>• perfect matched</li> <li>• high screening efficiency</li> <li>• Compliance with the class A standard</li> <li>• Compliance with the requirements of the MTBiGM regulation</li> <li>• Meets IEC68-2 Part 3 Accelerated Aging Standard</li> </ul>	...	<ul style="list-style-type: none"> <li>• Operation modes : Power consumption, Voltage, Cumulated amount of electricity, Cumulative cost of electricity, Cost of electricity ( \$/kWh )</li> <li>• Large, readable LCD display</li> <li>• Simple configuration of the cost calculation setting</li> </ul>
Manufacturer / Brand	...	...	BRATECK	UNI-T
LED diodes	Power, Link/Act, 10/100Mb, PoE, Uplink 10/100/1000 Mb/s	...	...	...
Certificates	FCC Class B, CE	...	...	...
Power supply	230 V AC	...	...	230 V AC, 50 Hz + 1 x CR2032
Housing type	Rack 19"	...	...	...
Weight	3.93 kg	45 kg/km	0.524 kg	0.165 kg
Dimensions	430 x 270 x 67 mm	...	115 x 115 x 88 mm	130 x 65 x 80 mm
Guarantee	2 years	5 years	2 years	2 years