




	<a href="#">ACCESS POINT 4G LTE +ROUTER TL-MR6400 300Mb/s TP-LINK</a>	<a href="#">NVR TC-R3880 SPEC:I/B/N/V4.0 80 CHANNELS TIANDY</a>	<a href="#">SWITCH POE GTX-A1-06-42-V2 4-PORT</a>
			
	77.45 EUR 77.45 EUR	1610.72 EUR 1610.72 EUR	33.04 EUR 33.04 EUR
Standard	...	IP	...
Frequency range	2.4 GHz	...	...
Supported resolutions	...	max. 16 Mpx	...
Video outputs	...	2 pcs HDMI 4K 2 pcs VGA Video outputs are independent of each other	...
Audio support	...	Audio from cameras	...
Audio inputs	...	1 pcs	...
Audio outputs	...	1 pcs	...
Antenna type	2 x WiFi built-in , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna	...	...
Management	...	...	—
Standards	802.11n/g/b IEEE 802.3/3u	...	...
Image compression method	...	S+265 / H.265 / S+264 / H.264	...
LED diodes	...	...	Power, S - Extend, PoE, Link/Act
Transmission speed	...	...	10 / 100 Mbps : 4 LAN & PoE ports + 2 Uplink ports
Supported hard drives	...	8 x 18 TB SATA + 1 x eSATA	...
Recording modes	...	Manual, Motion Detection, Schedule	...
Maximal output power	...	...	30 W / port PoE 802.3af/at - 1 ... 4 ports
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps	...	...
External storage devices backup	...	Backup to USB drive (pendrive, external drive)	...
Maximal total power	...	...	60 W

Searching and playback the records	...	<ul style="list-style-type: none"> <li>Records searching: by time and events type. Records playback: forward, backward, fast, slow</li> <li>Advanced searching (to the one second accuracy)</li> <li>Playback max. 16 cameras in the same time</li> </ul>	...
Modulation type	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM	...	...
Operation modes	...	...	<ul style="list-style-type: none"> <li>N - Normal - the device operates as normal PoE switch</li> <li>S - Extend - Range : 250 m @ 10 Mbps</li> </ul>
LAN ports	<ul style="list-style-type: none"> <li>1 x 10/100 Mbps - LAN/WAN</li> <li>3 x 10/100 Mbps - LAN</li> </ul>	...	<ul style="list-style-type: none"> <li>4 x RJ45 10/100 Base-T ( 4 x PoE (802.3af/at) ),</li> <li>2 x RJ45 10/100 Base-T - Uplink</li> </ul>
Certificates	...	...	CE
Network interface	...	2 x RJ-45 - 10 / 100 / 1000 Mbps	...
Receiver sensitivity	<ul style="list-style-type: none"> <li>11g 54M: -74dBm</li> <li>11n HT20: -71dBm</li> <li>11n HT40: -67dBm</li> </ul>	...	...
LTE	✓	...	...
QSS	✓	...	...
Network functions	...	Full support via network, Remote records copying, Web-Server built-in	...
WDS	✓	...	...
Housing	...	...	Desktop, Metal
ONVIF	...	✓	...
Bitrate	...	max. 640 Mbps	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Operation temp	0 °C ... 40 °C	...	-10 °C ... 55 °C
Default IP address	...	192.168.1.3	...
Permissible relative humidity	max. 95 % (non-condensing)	...	...
Main features	<ul style="list-style-type: none"> <li>SIM socket</li> <li>WPS/RESET button</li> </ul>	...	...
RTSP URL	...	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream	...
Web browser access ports	...	80, 443, 3000, 3001, 3002, 23002	...
PC client access ports	...	3000, 3001	...
Mobile client access ports	...	3000, 3001	...

Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>	...
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...
Alarm inputs / outputs	...	16 / 4	...
Motion Detection	...	✓	...
Intelligent image analysis	...	—	...
USB	...	2 x USB 2.0 + 1 x USB 3.0	...
RS232	...	1 pcs	...
RS485	...	1 pcs	...
Mouse support	...	✓	...
IR remote controller in the set	...	—	...
Main features	...	<ul style="list-style-type: none"> <li>• Possibility of operation the disks in RAID JBOD/0/1/5/6/10 array</li> <li>Support for Intelligent Image Analysis function, available in TIANDY cameras : <ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• abandoned/missing object</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• parking detection</li> <li>• heat map</li> <li>• scene changing</li> <li>• signal loss indication</li> <li>• License plate recognition</li> <li>• detection of persons on duty</li> <li>• detection of people gathering</li> <li>• Parking monitoring mode</li> <li>• protective helmet detection</li> <li>• people counting</li> <li>• advanced face capture features (max 100 000 faces in the database)</li> </ul> </li> </ul>	...
Power supply	9 V DC / 1 A (power adapter included)	100 V ... 240 V AC	100 ... 265 V AC
Weight	0.354 kg	7.8 kg	0.49 kg
Dimensions	202 x 141 x 34 mm	440 x 465 x 95 mm	145 x 100 x 32 mm
Supported languages	...	Polish, English, Albanian, Arabic, French, Spanish, Korean, Dutch, Hebrew, Portuguese, German, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	...
Manufacturer / Brand	TP-LINK	TIANDY	...
Guarantee	3 years	3 years	2 years