

	SPLITTER RI-3/1F-DS	SWITCH POE APTI-POE0802G-120W 8-PORT	CONNECTION BOX PUH-3P-M16
			
	6.78 PLN 6.78 PLN	270.40 PLN 270.40 PLN	10.40 PLN 10.40 PLN
Number of intakes	2
Number of inputs	1 pcs
Number of outputs	3 pcs
Number of terminals	2 x 3 pcs
LAN ports	...	10 x RJ45 (8 x PoE (802.3af/at))	...
"Index of Protection"	IP68
Frequency range	5 ... 2400 MHz
Voltage insulation	300 V
Cable diameter	Ø 3.5 ... Ø 10.2 mm
Management	...	—	...
Wire gauge	0.5 ... 1.5 mm ²
LED diodes	...	LAN, PoE	...
Attenuation	< 7.5 dB @ 5 MHz ... 40 MHz < 8.0 dB @ 40 MHz ... 1000 MHz < 9.5 dB @ 1000 MHz ... 1750 MHz < 10.5 dB @ 1750 MHz ... 2400 MHz
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port LAN, • 10 / 100 Mbps : 8 x LAN & PoE ports 	...
Maximal output power	...	30 W / port PoE	...
Maximal total power	...	120 W	...
MAC addresses table	...	2k	...
Main features	...	<ul style="list-style-type: none"> • 2 x Port Uplink • Range PoE : 200 m - The EXTEND mode enabled 	...
Certificates	...	CE	...
Power supply	...	230 V AC	...
Operation temp	...	0 °C ... 55 °C	...

Isolation between outputs	> 22 dB @ 5 MHz ... 40 MHz > 20 dB @ 40 MHz ... 1000 MHz > 20 dB @ 1000 MHz ... 1750 MHz > 20 dB @ 1750 MHz ... 2400 MHz
Possibility to pass the DC voltage to the preamplifier	max. 24 V / 0.8 A (for each output)
Shielding	✓
Manufacturer / Brand	...	APTI	...
Impedance	75 Ω
Weight	0.040 kg	0.74 kg	...
Dimensions	78 x 48 x 15 mm	220 x 143 x 41 mm	58 ... 65 x 21 x 21 mm
Guarantee	2 years	2 years	2 years