



	PATCHCORD RJ45/6/5.0-ORANGE 5 m	NVR NVR5416-16P-EI 16 CHANNELS, 16 PoE DAHUA
		
	1.73 EUR 1.73 EUR	1572.62 EUR 1572.62 EUR
Standard	...	TCP/IP
Cable	UTP cat. 6 : RJ-45 plug / RJ-45 plug	...
Supported resolutions	...	max. 32 Mpx - 11520 x 2700 px
Color	Orange	...
Length of the cable	5 m	...
Video outputs	...	2 pcs HDMI 4K 2 pcs VGA
Main features	Very easy and quick assembly	...
Audio support	...	16 Channels - Audio from cameras
Audio inputs	...	1 pcs CINCH
Audio outputs	...	2 pcs CINCH
Image compression method	...	H.265 / H.265+ / H.264 / H.264+ / MJPEG
USB	...	1 pcs USB 2.0 2 pcs USB 3.0
Supported hard drives	...	4 x 20 TB SATA III + 1 eSATA
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function
Bitrate	...	max. 384 Mbps
Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Default IP address	...	192.168.1.108

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Alarm inputs / outputs	...	16 / 6
PTZ control	...	IP Speed Dome Cameras
Motion Detection	...	22 x 18 motion zones - after motion detection records detected channels only
Intelligent image analysis	...	✓
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	<ul style="list-style-type: none"> • 16-port PoE Switch built-in, 25.5 W / Channel, PoE (802.3af/at) • ePoE - 800 m : 1 ... 8 ports
Maximum total switch load	...	150 W
Power supply	...	100 ... 240 V AC @ 50 / 60 Hz
Weight	0.13 kg	4.86 kg
Dimensions	...	440 x 415 x 76 mm
Supported languages	...	Polish, English, Bulgarian, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian
Country of origin	...	China
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years

