



	<a href="#">AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR APTI-XB0401-S31 4 CHANNELS</a>	<a href="#">WALL MOUNTING KIT USP-U30 FOR SOLAR PANELS</a>
		
	53.27 EUR 53.27 EUR	23.66 EUR 23.66 EUR
Material	...	Aluminum
Tilt angle adjustment:	...	15 ° ... 50 °
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Main features	...	Maximum power of the mounted panel : 80 W
Video inputs	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS	...
Video outputs	1 pcs HDMI 1 pcs VGA	...
Audio inputs	2 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Image compression method	H.265+ / H.265 / H.264+ / H.264	...
Image records resolutions	<ul style="list-style-type: none"> <li>• AHD / HD-TVI : 1296 x 1944 - 5M-N, 1024 x 1536 - 3M-N, 960 x 1080 - 1080N, 1280 x 720 - 720p,</li> <li>• HD-CVI 1280 x 1440 - 4M-N, 960 x 1080 - 1080N, 1280 x 720 - 720p</li> <li>• CVBS / PAL : 960 x 576</li> <li>• IP : max. 2592 x 1944 - 5 Mpx</li> </ul>	...
Recording speed adjustment	1 ... 12 fps @ 5M-N 1 ... 15 fps @ 4M-N 1 ... 18 fps @ 3M-N 1 ... 18 fps @ 1080N 1 ... 20 fps @ 720p 1 ... 25 fps @ 960H for each channel	...

Operation modes	<ul style="list-style-type: none"> <li>• 4 x AHD / HD-CVI / HD-TVI</li> <li>• max. 2 x AHD / HD-CVI / HD-TVI + max. 4 x IP @ 1080p</li> <li>• 9 x IP @ 5 Mpx (max)</li> </ul> <p>All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras</p>	...
Recording modes	Motion Detection, Schedule	...
Supported hard drives	1 x 8 TB SATA	...
External storage devices backup	Records backup at (.avi) format to USB (pendrive)	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time	...
Network functions	<ul style="list-style-type: none"> <li>• Network Client Software (iVMS320): live view, playback and backup of the records</li> <li>• IE browser: live view, playback and backup of the records and configuration of the recorder parameters</li> </ul>	...
Mobile phones support	<p>Port no.: 6000 or access by a cloud (P2P)</p> <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BitVision</a>, Android: Free application <a href="#">iVMS320</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a>, iOS: Free application <a href="#">iVMS320</a></li> </ul>	...
Default IP address	192.168.1.88	...
Default admin user / password	admin / 12345	...
Web browser access ports	80, 5000, 554	...
PC client access ports	80, 5000, 554	...
Mobile client access ports	80, 5000, 6000	...
Alarm inputs / outputs	—	...
PTZ control	RS-485 - PELCO-D/P	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...

USB	2 pcs USB 2.0	...
Mouse support	✓	...
IR remote controller in the set	—	...
Power supply	12 V DC / 2 A (power adapter included)	...
Color	Black	...
Weight	0.68 kg	0.94 kg (total)
Dimensions	260 x 226 x 46 mm	310 x 300 x 43 mm - each item
Supported languages	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian	...
Manufacturer / Brand	APTI	...
Guarantee	2 years	2 years