

	<a href="#">IP CAMERA IPC-HFW5442E-ASE-0360B-S3 WizMind S - 4 Mpx 3.6 mm DAHUA</a>	<a href="#">WIRELESS OPTICAL MOUSE UMY-1077-UGO</a>
		
	426.68 EUR 426.68 EUR	3.74 EUR 3.74 EUR
Standard	TCP/IP	...
External connector	...	USB 2.0
Sensor	1/1.8 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Frequency band	...	2.4 GHz
Supported operating systems	...	Windows XP/Vista/7/8/10, Linux
Main features	...	<ul style="list-style-type: none"> <li>• Number of buttons : 6</li> <li>• Range : 10 m</li> <li>• DPI adjustment</li> <li>• Automatic sleep mode</li> <li>• Plug &amp; Play</li> <li>• The ergonomic shape</li> </ul>
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	1200 / 1600 / 1800 dpi
Lens	3.6 mm	...
View angle	<ul style="list-style-type: none"> <li>• 88 ° (manufacturer data)</li> <li>• 85 ° (our tests result)</li> </ul>	...
Range of IR illumination	50 m	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Image compression method	AI H.265 / H.265+ / H.265 / AI H.264 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Smart audio detection</li> <li>• Compliance with the AAC standard</li> </ul>	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP, P2P	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	22.06	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 140 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• SSA - Smart Scene Adaptive - intelligent scene adaptation by automatically adjusting the exposure parameters to obtain a better image</li> <li>• SMD 3.0 - searching for an object classified as: human, motor vehicle</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Mirror - Mirror image</li> <li>• Motion Detection - classification of people and vehicles</li> <li>• Configurable Privacy Zones</li> <li>• Heat map - the selection in the image by corresponding colors the areas with different traffic</li> <li>• IVS analysis : intrusion, crossing the line (tripwire), parking detection, fast moving, detection of people gathering, face detection - advanced face capture features - supports 6 types of facial attributes extraction, people counting - support for 4 independent detection areas</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• ePoE,</li> <li>• 12 V DC / 520 mA</li> </ul>	2 x 1.5V, type AAA/LR03 battery (not included)
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 8.3 W @ PoE</li> <li>• ≤ 6.2 W @ 12 V</li> </ul>	...
Housing	Compact - Metal	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.6 kg	0.06 kg



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	193 x 71 x 66 mm	<ul style="list-style-type: none"> <li>• Mouse : 116 x 74 x 39 mm,</li> <li>• Receiver : 14 x 6 x 19 mm</li> </ul>
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	DAHUA	uGo
Guarantee	5 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00