

	BATTERY 12V/18AH-MWS	HD-CVI, PAL CAMERA HAC-HFW2401R-Z-IRE6-27135 - 3.7 Mpx 2.7 ... 13.5 mm - MOTOZOOM DAHUA	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR DHI-XVR4108HS-S2 8 CHANNELS DAHUA
			
	127.06 PLN 127.06 PLN	697.00 PLN 697.00 PLN	450.00 PLN 450.00 PLN
Battery capacity	18 Ah
Rated voltage	12 V
Battery charging current	max. 5.0 A
Sensor	...	1/3 " Progressive Scan CMOS	...
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery
Connector	M5 screw
Matrix size	...	4.1 Mpx	...
Standard	...	HD-CVI, PAL	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Battery lifetime	3 ... 5 years
Video inputs	8 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs	1 pcs HDMI 1 pcs VGA
Resolution	...	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p , 960 x 576 - PAL	...
IR illuminator support	...	ICR - Movable InfraRed filter	...
Audio inputs	• 1 pcs CINCH, • 8 - Audio support via coaxial cable, HD-CVI only
Audio outputs	1 pcs CINCH
Image compression method	H.264
Number of compression levels	6
Video output	...	• HD-CVI, 1 Vpp / 75 Ω • PAL, 1 Vpp / 75 Ω	...
OSD menu	...	OSD menu available via DAHUA recorder	...
Lens	...	2.7 ... 13.5 mm - Motozoom	...
View angle	...	96 ° ... 25 °	...

Image records resolutions	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 960 x 1080, 1280 x 720 • AHD-L / PAL : 960 x 576, 720 x 576 • IP : max. 2592 x 1944
S/N ratio	...	> 65 dB	...
Range of IR illumination	...	60 m	...
IR illuminator power adjustment	...	Automatic	...
Main features	...	<ul style="list-style-type: none"> • Motozoom lens • WDR - 120 dB - Wide Dynamic Range • ICR - Movable InfraRed filter • 2D-DNR / 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • AGC - Automatic Gain Control • Privacy zones • Motion Detection • Auto White Balance 	...
Power consumption	...	≤ 11.1 W	...
Maximal total frame rate	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 96 fps @ 960 x 1080 px, 120 fps @ 1280 x 720 px, • AHD / PAL : 200 fps @ 960 x 576 px, 200 fps @ 720 x 576 px • IP : 250 fps @ 2592 x 1944 px
Housing	...	Compact, Metal	...
"Index of Protection"	...	IP67	...
Operation temp	...	-30 °C ... 60 °C	...
Recording speed adjustment	<ul style="list-style-type: none"> 1 ... 25 fps @ 2592 x 1944 px - IP 1 ... 12 fps @ 960 x 1080 px 1 ... 15 fps @ 1280 x 720 px 1 ... 25 fps @ 960 x 576 px 1 ... 25 fps @ 720 x 576 px for each channel

Operation modes	<ul style="list-style-type: none"> • 8 x AHD / HD-CVI / HD-TVI / PAL @ 1080N • 7 x AHD / HD-CVI / HD-TVI / PAL @ 1080N + 1 x IP @ 5 Mpx • 6 x AHD / HD-CVI / HD-TVI / PAL @ 1080N + 2 x IP @ 5 Mpx • 5 x AHD / HD-CVI / HD-TVI / PAL @ 1080N + 3 x IP @ 5 Mpx • 4 x AHD / HD-CVI / HD-TVI / PAL @ 1080N + 4 x IP @ 5 Mpx • 3 x AHD / HD-CVI / HD-TVI / PAL @ 1080N + 5 x IP @ 5 Mpx • 2 x AHD / HD-CVI / HD-TVI / PAL @ 1080N + 6 x IP @ 5 Mpx • 1 x AHD / HD-CVI / HD-TVI / PAL @ 1080N + 7 x IP @ 5 Mpx • 8 x AHD / HD-CVI / HD-TVI / PAL / IP + 2 x IP @ 5 Mpx <p>All modes allow for any combination of the AHD-H, HD-CVI, HD-TVI, PAL cameras</p>
Recording modes	Manual, Motion Detection, Schedule
Supported hard drives	1 x 8 TB SATA
External storage devices backup	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters

Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Alarm inputs / outputs	—
PTZ control	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P and others
Motion Detection	Split the screen into zones : 22 x 18 motion zones
Mouse support	✓
IR remote controller in the set	—
Power supply	...	12 V DC / 920 mA	12 V DC / 2 A (power adapter included)
Color	...	White	Black
Weight	4.5 kg	0.59 kg	0.94 kg
Dimensions	180 x 165 x 75 mm	213 x 90 x 90 mm	260 x 236 x 48 mm
Supported languages	English, Bulgarian, Czech, Finnish, Greek, Polish, Romanian, Serbian, Slovenian, Hungarian
Country of origin	China
Manufacturer / Brand	...	DAHUA	DAHUA
Guarantee	2 years	3 years	3 years