



| | | |
|--|--|--|
| | SMART VALVE FOR THE IRRIGATION SYSTEM ATLO-VR1C-BLE-TUYA Bluetooth BLE, Tuya Smart | SMART LIGHT SWITCH ATLO-WB1/K-TUYA Wi-Fi, Tuya Smart |
| |  |  |
| | 24.59 EUR 24.59 EUR | 9.53 EUR 9.53 EUR |
| Application | irrigation control | Works with lighting - switching on/off |
| Type (size) | 3/4 " | ... |
| Working pressure | 0.02 ... 0.8 MPa / 2.9 ... 116 psi | ... |
| Rated voltage | ... | 100 ... 240 V AC, 50 / 60 Hz |
| Maximum power | ... | 600 W |
| Water flow | 13 ... 33 l/min | ... |
| Rated current | ... | max. 10 A |
| Opening/closing time | 5 ... 10 s | ... |
| Number of buttons | ... | 1 |
| Number of outputs | ... | 1 |
| Radio communication range (at open area) | 15 m | ... |
| Connector type | ... | screw terminals |
| Wireless | Bluetooth | Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n |
| Mobile phones support | <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS | <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS |
| Permissible relative humidity | ... | ≤ 80 % |

| | | |
|-----------------------|--|--|
| Main features | <ul style="list-style-type: none"> • schedule - 20 tasks, • timer, • manual watering (app or button), • delay after rain : 24, 48, 72 h - the device will not turn on the sprinklers if it is raining, • remote access - Bluetooth/Wi-Fi gateway, • voice control • STATUS indicator • Low current consumption • Easy installation - the valve is mounted directly on the tap • 3/4" / 1/2" Adapter (included) | <ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication |
| Housing | Plastic (ABS) + Nylon, UV-resistant, Waterproof | Plastic |
| "Index of Protection" | IP55 | ... |
| Color | Black + Green | White |
| Power supply | 2 x 1.5V, type AA/LR6/FR6 battery (not included) | ... |
| Operation temp | 4.5 °C ... 45 °C | -20 °C ... 50 °C |
| Weight | 0.19 kg | 0.089 kg |
| Dimensions | 137 x 68 x 89 mm | 87 x 86 x 41 mm |
| Guarantee | 2 years | 2 years |