




	<a href="#">INDOOR SIREN SPW-220-R SATEL</a>	<a href="#">INDOOR SIREN SV-96BE</a>	<a href="#">CONNECTOR WITH ELASTIC SEALING F/5.9-G</a>
			
	22.70 EUR 22.70 EUR	4.43 EUR 4.43 EUR	0.12 EUR 0.12 EUR
Sound pressure level	...	109 dB/m	...
Current consumption	max. 290 mA	...	...
Connector type	...	...	"F" Straight plug
Attachment of connector elements	...	...	Twisted-on
Shield fastening	...	...	Twisting-on
Wire mounting	...	...	—
Application	...	...	Coaxial cable
Main features	...	<ul style="list-style-type: none"> <li>• Piezoelectric transducer</li> <li>• LED SMD diodes</li> <li>• Plastic (ABS)</li> <li>• Power cord : 40 cm</li> </ul>	...
Cable diameter	...	...	max. 5.9 mm
Impedance	...	...	75 Ω
Maximal current consumption	...	150 mA	...
Material	...	...	Metal
Internal backup battery	...	—	...
Example of application	...	...	RG59
Power supply	12 V DC ± 15% (powering from external adapter)	13.8 V DC	...
Color	Red	White / LED indication - Blue	...
Manufacturer / Brand	SATEL	...	...
Main features	...	...	<ul style="list-style-type: none"> <li>• Wide frequency range</li> <li>• Corrosion resistance</li> <li>• Elastic sealing</li> </ul>
Operation temp	-10 °C ... 55 °C	-35 °C ... 60 °C	...
Weight	0.145 kg	0.09 kg	0.0032 kg
Dimensions	87 x 134 x 37 mm	122 x 74 x 44 mm	Ø 11 mm x 20 mm
Guarantee	2 years	2 years	2 years