



	<a href="#">POWER DISTRIBUTION UNIT AK-SP-05A AKYGA</a>	<a href="#">VIDEO SEPARATOR D-SEP/HD-4</a>
		
	9.09 EUR 9.09 EUR	20.43 EUR 20.43 EUR
Rated voltage	230 V AC / 50 Hz	...
Total maximal current	10 A	...
Maximal total load	2500 W	...
Response time	< 25 ns	...
Number of outlets	5 grounded outlets 10A/250V	...
Automatic delayed fuse	10 A / 250 V	...
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Standard	...	<ul style="list-style-type: none"> <li>• AHD - 8 Mpx, 4K UHD</li> <li>• HD-CVI - 8 Mpx, 4K UHD</li> <li>• HD-TVI - 8 Mpx 4K UHD</li> <li>• CVBS - PAL / NTSC</li> </ul>
DC filter to eliminate interferences	RFI $\leq$ 10 dB	...
Device type	...	Passive
Maximum stroke current	4.5 kA	...
Number of inputs	...	4 pcs BNC socket
Maximum energy absorption	150 J	...
Number of outputs	...	4 pcs BNC socket
Input impedance	...	75 $\Omega$
Switch	with light indication	...
Output impedance	...	75 $\Omega$
Length of the cable	1.8 m	...
Opto-isolation between inputs and outputs	...	50 V DC
Housing	Plastic (ABS)	...
Galvanic separation between individual channels	...	> 2000 V
Color	Black	...
Attenuation	...	<ul style="list-style-type: none"> <li>• 4.43 MHz @ 0.37 dB</li> <li>• 11 MHz @ 0.47 dB</li> <li>• 21 MHz @ 0.62 dB</li> <li>• 38 MHz @ 0.93 dB</li> <li>• 42 MHz @ 0.93 dB</li> <li>• 67.5 MHz @ 1.16 dB</li> </ul>
Bandwidth	...	200 MHz

Inputs protection	...	ESD, IEC 61000-4-2, $\pm 30\text{kV}$ contact, $\pm 30\text{kV}$ air EFT, IEC 61000-4-4, 40A (5/50ns) Lightning, IEC 61000-4-5, 30A ( $t_p=8/20\mu\text{s}$ )
Power supply	...	—
Operation temp	5 °C ... 50 °C	-20 °C ... 55 °C
Weight	0.306 kg	0.12 kg
Dimensions	305 x 50 x 40 mm	103 x 78 x 30 mm
Manufacturer / Brand	AKYGA	DELTA
Guarantee	2 years	3 years