

	<a href="#">HDD ENCLOSURE Y-3036 UNITEK</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR PTZ85260-HNF-PA - 1080p, 5.6 ... 336 mm DAHUA</a>	<a href="#">CABLE MANAGER TRSH-8-BL*P10</a>
			
	12.32 EUR 12.32 EUR	8966.66 EUR 8966.66 EUR	1.34 EUR 1.34 EUR
Standard	...	TCP/IP	...
Sensor	...	1/1.8 " Progressive Scan CMOS	...
Supported hard drives	1 x SATA III, 2.5 "	...	...
Matrix size	...	2.1 Mpx	...
In package	...	...	<b>10 pcs The price for package</b>
Hole diameter	...	...	Ø 8 mm
Outputs	1 x USB 3.1, max. 5 Gb/s	...	...
Assembly	...	...	The bottom layer is equipped with a Scotch tape
Operation state indication	LED diodes	...	...
Material	...	...	Plastic
Resolution	...	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Scanning system	...	Progressive	...
Lens	...	5.6 ... 336 mm	...
View angle	...	56.4 ° ... 1.2 ° (manufacturer data)	...
Optical zoom	...	x 60	...
Digital zoom	...	x 16	...
Range of IR illumination	...	400 m	...
Video output	...	1 Vpp / 75 Ω	...
Preset rotation speed	...	• 160 °/s (horizontal) • 60 °/s (vertical)	...
Rotation speed (manual control)	...	• 0.1 °/s ... 160 °/s (horizontal) • 0.1 °/s ... 60 °/s (vertical)	...
Horizontal rotation range	...	360 ° continuous	...
Vertical rotation range	...	-90 ° ... 45 °	...
RS-485 interface	...	✓	...
Protocols	...	Pelco-D, Pelco-P, DH-SD Auto detection	...
Number of presets	...	300	...
Horizontal scan	...	✓	...
Route settings	...	8	...
Image compression method	...	H.265 / H.264H / H.264B / H.264 / MJPEG	...
Alarm inputs / outputs	...	7 / 2	...
Audio	...	• 1 Audio input • 1 Audio output • Bi-directional audio streaming support	...
Main stream frame rate	...	1 ... 25 fps - 1080p	...
Network interface	...	10/100 Base-T (RJ-45)	...
Network protocols	...	IPv4/IPv6, HTTP, HTTPS, IEEE 802.1x, QoS, FTP, SMTP, UPnP, SNMPv1/v2c/v3(MIB-2), DNS, DDNS, NTP, RTSP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE	...
WEB Server	...	Built-in, NVR compliance	...
Max. number of on-line users	...	20	...
ONVIF	...	✓	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default IP address	...	192.168.1.108	...
Default admin user / password	...	admin / -	...
Web browser access ports	...	80, 37777	...
PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)	...
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• EIS - Electronic Image Stabilization</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• ICR - Movable InfraRed filter</li> <li>• WB - White Balance (ATW/AWB/manual/indoor/outdoor)</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones - 24</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Lens wiper remotely controlled via TCP/IP</li> <li>• IVS analysis : Intelligent Object Tracking, crossing the line (tripwire), intrusion, abandoned/missing object, scene changing, Face recognition, metadata support, classification of people and vehicles, Filtering of false alarms based on the recognition of persons and vehicles (tripwire, intrusion)</li> </ul>	...
Power supply	Port USB	36 V DC / 2.23 A (power adapter included)	...
Power consumption	...	<ul style="list-style-type: none"> <li>• 28.7 W</li> <li>• 61.6 W ( LED IR, PTZ, Wiper )</li> </ul>	...
Housing	Desktop, Plastic	Metal	...
Color	...	Gray + Black	Blue
"Index of Protection"	...	IP67	...
Operation temp	...	-40 °C ... 70 °C	...
Weight	0.08 kg	14.9 kg (with bracket)	...
Dimensions	131 x 83 x 35 mm	211 x 400 x 517 mm (with bracket)	...
Supported languages	...	English	...
Manufacturer / Brand	UNITEK	DAHUA	...
Guarantee	2 years	5 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00