



	THERMOSTAT ZR-011	SWITCH POE SG1006P 4-PORT DAHUA
		
	17.81 CAD 17.81 CAD	57.10 CAD 57.10 CAD
Sensor type	Bimetallic	...
Contact type	<ul style="list-style-type: none"> • 1 pcs NC - opened after exceeding the set temperature, • 1 pcs NO - closed after exceeding the set temperature Each contact has its own temperature setting	...
Maximal power voltage	250 V AC	...
Relay maximal load	10 A	...
LAN ports	...	<ul style="list-style-type: none"> • 4 x RJ45 10/100/1000 Base-T (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink
Management	...	—
Temperature set range	0 °C ... 60 °C	...
Hysteresis	7 °C ± 4 °C	...
LED diodes	...	Power, PoE, Link/Act
"Index of Protection"	IP20	...
Transmission speed	...	10 / 100 / 1000 Mbps : 4 LAN & PoE ports + 2 Uplink ports
Assembly	DIN TS-35 rail	...
Maximal output power	...	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports
Maximal total power	...	60 W
MAC addresses table	...	2k
Operation modes	...	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6

Main features	...	<ul style="list-style-type: none"> • PoE power mode : The device supports 8-pin power supply • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Kensington Lock • Possibility to mount to the wall
Certificates	...	CE
Protections	...	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing	...	Desktop, Metal
Power supply	...	53 V DC / 1.22 A (power adapter included)
Operation temp	-20 °C ... 80 °C	-10 °C ... 55 °C
Weight	0.090 kg	0.29 kg
Dimensions	65 x 50 x 46 mm	130 x 85 x 26 mm
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years