



	CONVERTER SDI/VGA+A	INTERFACE OF INPUTS RNW-01 Wi-Fi SUPLA ZAMEL
		
	30.38 EUR 30.38 EUR	42.06 EUR 42.06 EUR
Support	...	SUPLA
Application	...	controlling devices, triggering actions
Rated voltage	...	230 V AC
Inputs	1 pcs SDI / HD-SDI / 3G-SDI (BNC socket)	...
Maximal total load	...	—
Total maximal current	...	—
Number of inputs	...	4
Outputs	1 pcs VGA (D-Sub 15-pin) 1 pcs SDI/HD-SDI/3G-SDI (BNC socket - loop through) 1 pcs Audio Coaxial 1 pcs Audio stereo (Cinch)	...
Number of outputs	...	0
Connector type	...	Connection cube, screw terminals
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Radio communication range	...	The range limited only by the availability of the Wi-Fi network
SDI supported standards	<ul style="list-style-type: none"> • SD-SDI: SMPTE 259M-C, 270 Mbps • HD-SDI: SMPTE 292M 1.485 & 1.485 / 1.001 Gb/s • 3G-SDI: SMPTE 424M/425M-AB 2.970 & 2.970 / 1.001 Gb/s 	...
Mobile phones support	...	<ul style="list-style-type: none"> • The SUPLA free application on Android • The SUPLA free application on iOS
Maximal length of the SDI cable	3G/HD/SD-SDI to 100 m / 200 m / 300 m	...
Supported VGA resolutions	VGA ... WUXGA 480p ... 1080p	...

ESD protection	± 8 kV (air-gap discharge) ± 4 kV (contact discharge)	...
Main features	...	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API
Power supply	5 V DC / 2.6 A (power adapter included)	...
Housing	...	Plastic
Power consumption	9 W	...
"Index of Protection"	...	IP20
Color	...	Green
Operation temp	...	-20 °C ... 50 °C
Operation temp. / Relative humidity	0 °C ... 40 °C / 20 % ... 90 % (non-condensing)	...
Weight	0.470 kg	0.033 kg
Dimensions	180 x 143 x 25 mm	47 x 47 x 20 mm
Manufacturer / Brand	...	ZAMEL
Guarantee	2 years	2 years