




	HUB USB 3.0 HUB-USB3.0-1/4 55 cm	RFID PROXIMITY CARD ATLO-114	AHD, HD-CVI, HD-TVI CAMERA BCS-EA25FSR3(H2) - 5 Mpx 2.8 mm
			
	6.24 EUR 6.24 EUR	0.57 EUR 0.57 EUR	46.15 EUR 46.15 EUR
Standard	...	Unique EM 125kHz	...
Compatibility	...	EM4100/4102	...
Possibility of programming the serial number (ID)	...	—	...
Ability to write to internal memory	...	—	...
Standard	AHD / HD-CVI / HD-TVI / CVBS
Serial Number overprint	...	—	...
Connectors	<ul style="list-style-type: none"> • 1 x socket - USB 3.0 Micro B • 4 x socket - USB 3.0 A • 1 x Power socket - 1.35 / 3.50 mm
Length of the cable	55 cm
USB standard	3.0
Main features	<ul style="list-style-type: none"> • Solid workmanship • It can be used as a charger for multiple devices when connected to an external power source via the 3.50 / 1.35 mm socket • LED indication • The cable included in the kit: USB 3.0 A plug / USB 3.0 Micro B plug • Each socket has a separate switch 	<ul style="list-style-type: none"> • Range : ~ 15 cm • The TK-4100 chip 	...
Resolution	2704 x 1950 - 5 Mpx @ AHD / HD-TVI @ 20 fps , 2560 x 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-CVI @ 25 fps 1920 x 1080 - 1080p - AHD, HD-TVI, HD-CVI @ 25 fps
Sensor	1/2.8 " Progressive Scan CMOS
Lens	2.8 mm, F1.2
View angle	103 °
Range of IR illumination	30 m

S/N ratio	> 50 dB
Video output	AHD / HD-CVI / HD-TVI, 1 Vpp / 75 Ω
OSD menu	✓
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio output
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • BLC - configurable Back Light Compensation • 3D-DNR - Digital Noise Reduction • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance
Power supply	12 V DC / 420 mA
Power consumption	< 5 W
Housing	Dome, Metal
Color	White
"Index of Protection"	IP66
Mechanical protection class	—
Operation temp	-20 °C ... 60 °C
Weight	0.044 kg	0.006 kg	0.3 kg
Dimensions	105 x 36 x 25 mm	85 x 54 x 2 mm	Ø 94 x 80 mm
Manufacturer / Brand	...	ATLO	BCS
Guarantee	2 years	2 years	3 years