



| | | |
|------------------------------|--|---|
| | IP CAMERA DS-2CD2323G2-IU(2.8MM)(D) ACUSENSE - 1080p Hikvision | MICROPHONE CABLE KM-4/M |
| |  |  |
| | 226.57 EUR 226.57 EUR | 0.38 EUR 0.38 EUR |
| Standard | TCP/IP | ... |
| Sensor | 1/2.8 " Progressive Scan CMOS | ... |
| In section | ... | 100 m . Price for 1m when buying a whole roll |
| Matrix size | 2.1 Mpx | ... |
| Inner conductor | ... | Cu Stranded wire : 20 x 0.12 mm |
| Shield | ... | PVC |
| Resolution | 1920 x 1080 - 1080p , 1280 x 720 - 720p | ... |
| Lens | 2.8 mm | ... |
| Braid | ... | Cu Stranded wire : 32 x 0.1 mm |
| View angle | 107 ° | ... |
| Outer coating | ... | Ø 4.0 mm PVC |
| Coating color | ... | Black |
| Range of IR illumination | 30 m | ... |
| S/N ratio | ≥ 52 dB | ... |
| RS-485 interface | — | ... |
| Memory card slot | Micro SD memory cards up to 256GB support (possible local recording) | ... |
| Image compression method | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... |
| Alarm inputs / outputs | — | ... |
| Audio | <ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Noise suppression and echo cancellation | ... |
| Main stream frame rate | 25 fps @ 1080p | ... |
| Network interface | 10/100 Base-T (RJ-45) | ... |
| WEB Server | Built-in | ... |
| Max. number of on-line users | 6 | ... |
| ONVIF | ✓ | ... |

| | | |
|-------------------------------|---|-----|
| Main features | <ul style="list-style-type: none"> • Camera from AcuSense series • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • NAS - Network Attached Storage support • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • BLC/HLC - Back Light / High Light Compensation • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Configurable Privacy Zones • Vertical or horizontal image mirror • Filtering of false alarms based on the recognition of persons and vehicles • Smart motion detection (with recognizing people and vehicles) • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection | ... |
| Mobile phones support | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect | ... |
| Default IP address | 192.168.1.64 | ... |
| Default admin user / password | admin / - The administrator password should be set at the first start | ... |
| Web browser access ports | 80 | ... |
| PC client access ports | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application | ... |
| Mobile client access ports | 8000 | ... |
| Port ONVIF | 80 | ... |
| RTSP URL | <ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization | ... |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA | ... |

| | | |
|-----------------------|---|---------|
| Power consumption | <ul style="list-style-type: none"> • ≤ 7.5 W @ PoE (802.3af) • ≤ 6 W @ 12 V DC | ... |
| Housing | Dome, Metal | ... |
| Color | White | ... |
| "Index of Protection" | IP67 | ... |
| Vandal-proof | — | ... |
| Operation temp | -30 °C ... 60 °C | ... |
| Weight | 0.73 kg | ... |
| Dimensions | Ø 127 x 96 mm | ... |
| Supported languages | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian | ... |
| Manufacturer / Brand | Hikvision | ... |
| SAP Code | 311319958 | ... |
| Guarantee | 3 years | 2 years |

