

	BATTERY 12V/0.8AH-UL ULTRACELL	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE78H0T- IT3F(2.8MM)(C) - 5 Mpx Hikvision
		
	6.81 EUR 6.81 EUR	75.33 EUR 75.33 EUR
Battery capacity	0.8 Ah	...
Rated voltage	12 V	...
Battery charging current	< 0.24 A	...
Standard	...	AHD / HD-CVI / HD-TVI / CVBS
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery	...
Sensor	...	Progressive Scan CMOS
Connector	JST	...
Matrix size	...	5 Mpx
Battery lifetime	3 ... 5 years	...
Resolution	...	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI, • 1920 x 1080 - 1080p @ HD-TVI • 960 x 576 - 960H @ PAL
Range of IR illumination	...	40 m
IR illuminator power adjustment	...	Automatic
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 85 ° (manufacturer data) • 80 ° (our tests result)
IR illuminator support	...	ICR - Movable InfraRed filter
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω

Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	...	OSD menu available via recorder
Power supply	...	12 V DC / 340 mA
Power consumption	...	≤ 4.3 W
Housing	...	Dome, Metal + Plastic
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	0.34 kg	0.3 kg
Dimensions	25 x 96 x 62 mm	Ø 110 x 91 mm
Manufacturer / Brand	ULTRACELL	Hikvision
SAP Code	...	300613613
Guarantee	2 years	3 years