





	3 PCS SET ACCESS POINT +ROUTER MAX18-3 Wi-Fi 6, 2.4 GHz, 5 GHz DAHUA	HUB USB 3.0 PAPW4A-U3-015-BK-EP	ROUTER WIFI RG-EG105GW-X Wi-Fi 6, 574 Mbps + 2404 Mbps REYEE	PROJECTOR MOUNT PD-670
				
	285.47 CAD 285.47 CAD	10.57 CAD 10.57 CAD	352.23 CAD 352.23 CAD	22.46 CAD 22.46 CAD
Bearing capacity	20 kg
In package	3 pcs
Connectors	...	<ul style="list-style-type: none"> • 1 x plug - USB-A • 4 x socket - USB-A
Length of the cable	...	15 cm
Frequency range	2.4 GHz, 5 GHz	...	2.4 GHz, 5 GHz	...
USB standard	...	3.0
Distance from mounting surface	<ul style="list-style-type: none"> • 430 ... 650 mm (vertical), • 350 ... 560 mm (horizontal)
Projector mounting holes distances	Ø 225 ... 316 mm
Tilt adjustment	-15 ° ... 15 °
Antenna type	<ul style="list-style-type: none"> • 2.4 GHz : 2 x pcs Omnidirectional antenna - built-in • 5 GHz : 2 x Omnidirectional antenna - built-in 	...	2x2 MIMO - built-in <ul style="list-style-type: none"> • 5 dBi @ 2.4 GHz • 5 dBi @ 5 GHz 	...
Horizontal rotation	-8 ° ... 8 °
Color	Silver
Material	Steel - powder painted
Standards	<ul style="list-style-type: none"> • LAN : IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, • Wi-Fi : IEEE 802.11 b/g/n/ac/ax 	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6	...
Baud rates	574 Mbps + 1201 Mbps	...	574 Mbps @ 2.4 GHz + 2404 Mbps @ 5 GHz	...
LAN ports	3 x 10/100/1000 Mbps	...	<ul style="list-style-type: none"> • 1 x LAN 10/100/1000 Mbps (RJ-45) • 3 x LAN/WAN 10/100/1000 Mbps (RJ-45) 	...
WAN interface	1 x WAN x 10/100/1000 Mbps (RJ-45)	...
LED indicators	Status, Link/Act, Mesh	...
DDNS	✓	...
DHCP server	✓	...
Port USB	✓	...
Firmware update	✓	...
Power supply PoE	—	...

Protections	WPA2	...	<ul style="list-style-type: none"> • TCP scan blocking • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping • Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks 	...
Management interface	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reyeeye application • Remote management • Web browser 	...
Mobile phones support	<p>Android: Free application Ruijie Reyeeye</p> <p>iOS (iPhone): Free application Ruijie Reyeeye</p>	...
Main features	<ul style="list-style-type: none"> • Support for Mesh technology, • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • Port Security : Contact/Air (ESD/EMP) $\pm 8 \text{ kV} / \pm 6 \text{ kV}$ • Easy and uniform management system for many devices - WiLynk application • Intuitive installation and configuration of many advanced functions 	...	<ul style="list-style-type: none"> • Support for Reyeeye Mesh technology • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button 	Possibility to mount on the wall or ceiling
Power supply	12 V DC / 1.5 A (power adapter included)	...	100 ... 240 V AC, 50 / 60 Hz	...
Power consumption	$\leq 12 \text{ W}$...	$\leq 20 \text{ W}$...
Operation temp	-10 °C ... 55 °C	...	0 °C ... 40 °C	...
Permissible relative humidity	5 % ... 95 %	...	10 % ... 90 % (non-condensing)	...
Weight	0.23 kg	0.035 kg	1.1 kg	1.5 kg
Dimensions	95 x 95 x 73 mm	98 x 34 x 13 mm	315 x 188 x 188 mm	...
Manufacturer / Brand	DAHUA	ORICO	RUIJIE / REYEE	...
Guarantee	2 years	2 years	2 years	2 years