




	FIBER OPTIC CABLE GYFXTH-4/500M	CONNECTOR FOR LED STRIPS AD-TL-6499/Z/T 8 mm ORNO	CABLE CLIP SET TRSH-SET
			
	199.79 EUR 199.79 EUR	0.89 EUR 0.89 EUR	2.68 EUR 2.68 EUR
Strip width	...	8 mm	...
Fiber type	Single-mode, ITU-T G.652.D, U-DQ(ZN)BH
Number of fibers	4 pcs
"Index of Protection"	...	—	...
Cable diameter	5.8 mm
Maximal power voltage	...	48 V	...
Weight	...	0.002 kg	...
Length	It is sold in 500 m spools
Dimensions	...	25 x 17 mm	...
Manufacturer / Brand	...	ORNO	...
Buffer diameter	250 µm
Maximum pulling force	2000 N (dynamic)
Minimal bend radius	116 mm (during installation)
Main features	<ul style="list-style-type: none"> • rodent protected • the LSZH (or LSOH) jacket - zero halogen, flame retardant and low smoke • gel-filled central tube • reinforced by aramid yarn • ripcord making it easier to cut the outer sheath of the cable
Number of pcs. in package	10 pcs (total) <ul style="list-style-type: none"> • 2 pcs : 65 mm x 27 mm x 11 mm • 2 pcs : 33 mm x 33 mm x 15 mm • 2 pcs : 34 mm x 34 mm x 12 mm • 2 pcs : 28 mm x 28 mm x 16 mm • 2 pcs : 28 mm x 28 mm x 15 mm

Application	<ul style="list-style-type: none"> • due to the small size and flexibility, the cables are ideal for installation in cable ducts • it is used in modern FTTH and FTTB systems, in server rooms, between buildings installations • universal fiber optic cables intended for horizontal connections in buildings and outside buildings in secondary sewage system 	Works with LED lighting	...
Operation temp	-40 °C ... 60 °C
Installation temperature	-5 °C ... 70 °C
Holes dimensions	<ul style="list-style-type: none"> • 2 pcs : 5 x Ø 6 mm • 2 pcs : 3 x Ø 6 mm • 2 pcs : 2 x Ø 6 mm • 2 pcs : 1 x Ø 6 mm • 2 pcs : 2 x Ø 5 mm
Assembly	The bottom layer is equipped with a Scotch tape
Color	...	White	Black
Material	Plastic
Guarantee	2 years	2 years	2 years

