

	<a href="#">SMART SWITCH WITH TEMPERATURE MEASUREMENT ATLO-TSH1-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">SMART VALVE FOR THE IRRIGATION SYSTEM ATLO-VRIC-BLE-TUYA Bluetooth BLE, Tuya Smart</a>
		
	30.76 CAD 30.76 CAD	35.55 CAD 35.55 CAD
Type (size)	...	3/4 "
Application	<ul style="list-style-type: none"> <li>• Temperature measurement,</li> <li>• switching devices on/off</li> </ul>	irrigation control
Working pressure	...	0.02 ... 0.8 MPa / 2.9 ... 116 psi
Temperature measurement	-40 °C ... 80 °C ± 0.5 °C	...
Water flow	...	13 ... 33 l/min
Opening/closing time	...	5 ... 10 s
Maximal total load	3750 W	...
Radio communication range (at open area)	...	15 m
Total maximal current	15 A	...
Number of inputs	1	...
Number of outputs	2	...
Connector type	screw terminals	...
Wireless	<ul style="list-style-type: none"> <li>• Wi-Fi 2.4 GHz IEEE 802.11 b/g/n</li> <li>• Bluetooth</li> </ul>	Bluetooth
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>

Main features	<ul style="list-style-type: none"> <li>• Warning indication about exceeding the preset temperature,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Pairing button,</li> <li>• Wi-Fi indicator,</li> <li>• Temperature history graph,</li> <li>• For indoor use</li> </ul>	<ul style="list-style-type: none"> <li>• schedule - 20 tasks,</li> <li>• timer,</li> <li>• manual watering (app or button),</li> <li>• delay after rain : 24, 48, 72 h - the device will not turn on the sprinklers if it is raining,</li> <li>• remote access - Bluetooth/Wi-Fi gateway,</li> <li>• voice control</li> <li>• STATUS indicator</li> <li>• Low current consumption</li> <li>• Easy installation - the valve is mounted directly on the tap</li> <li>• 3/4" / 1/2" Adapter (included)</li> </ul>
Housing	Plastic	Plastic (ABS) + Nylon, UV-resistant, Waterproof
"Index of Protection"	...	IP55
Color	White	Black + Green
Permissible relative humidity	0 % ... 90 % (non-condensing)	...
Power supply	90 ... 250 V	2 x 1.5V, type AA/LR6/FR6 battery (not included)
Operation temp	0 °C ... 40 °C	4.5 °C ... 45 °C
Weight	0.1 kg (total)	0.19 kg
Dimensions	<ul style="list-style-type: none"> <li>• 96 x 54 x 28 mm</li> <li>• 95 cm (cable length) Probe</li> </ul>	137 x 68 x 89 mm
Guarantee	2 years	2 years