



	<a href="#">SMART CONTROLLER FOR ROLLER SHUTTERS SRW-02M Wi-Fi 230 V AC ZAMEL</a>	<a href="#">IP CAMERA APTI-AI802C6-60W - 8.3 Mpx 4K UHD 6 mm</a>
		
	158.21 AUD 158.21 AUD	152.38 AUD 152.38 AUD
Standard	...	TCP/IP
Support	SUPLA	...
Application	roller shutters, roof windows, awnings, drop-down screens, curtains	...
Matrix size	...	8.3 Mpx
Number of inputs	4	...
Sensor	...	1/2.8 " SONY Starvis™ Back-illuminated CMOS
Number of outputs	2 ( Motors )	...
Rated voltage	230 V AC	...
Relay maximal load	5 A	...
Maximal outputs load	350 W (single output)	...
Connector type	screw terminals	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Resolution	...	3840 x 2160 - 8.3 Mpx 4K UHD , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	6 mm
View angle	...	53 °
Range of IR illumination	...	60 m
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate	...	20 fps @ 8.3 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Main features	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Possibility to manually program scenarios from the built-in API</li> </ul>	...
Memory card slot	...	—
Alarm inputs / outputs	...	—

Operation temp	-10 °C ... 55 °C	...
Audio	...	<ul style="list-style-type: none"> <li>• External microphone input - Cinch socket,</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> </ul>
WEB Server	...	Built-in
Max. number of on-line users	...	10
ONVIF	...	✓
RS-485 interface	...	—
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">SUPLA</a> free application on Android</li> <li>• The <a href="#">SUPLA</a> free application on iOS</li> </ul>	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BitVision</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a></li> </ul>
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / admin The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	80
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> <li>• rtsp://user:password@ip_address:80/0 - Main stream</li> <li>• rtsp://user:password@ip_address:80/1 - Sub stream</li> </ul>

Main features	...	<ul style="list-style-type: none"> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), loitering detection, detection of people gathering, motion detection based on human detection</li> <li>• WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• Mirror - Mirror image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Day/Night mode - configurable</li> <li>• RESET button - on the cable</li> <li>• Privacy zones - max. 3</li> <li>• Sharpness - sharper image outlines</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 530 mA</li> </ul>
Power consumption	...	≤ 6.4 W
Housing	Plastic	Compact - Metal
Color	Green	White
"Index of Protection"	IP20	IP67
Operation temp	...	-20 °C ... 60 °C
Weight	0.127 kg	0.45 kg
Dimensions	90 x 66 x 35 mm	173 x 73 x 73 mm
Supported languages	...	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	ZAMEL	APTI
Guarantee	2 years	2 years