



	SMART LED LIGHTING CONTROLLER WLIGHTBOX-V3/BLEBOX Wi-Fi, 12 ... 24 V DC	SMART SWITCH SWITCHBOX-DIN/BLEBOX Wi-Fi, 230 V AC
		
	32.83 EUR 32.83 EUR	46.43 EUR 46.43 EUR
Application	Works with LED lighting - (RGB/RGBW/RGBCCT/CCT/MONO) 12-24V LED strips	switching devices on/off
Rated voltage	12 ... 24 V DC	230 V AC
Maximal total load	360 W	3680 W (resistance load) / 500 W (inductive or capacitive load)
Total maximal current	15 A (3 A / Channel)	16 A
Number of inputs	1	2
Number of outputs	5	1
Connector type	screw terminals	screw terminals
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS 	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS

Main features	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • Controlling the color, color temperature, brightness, effect, changing time allows any interior arrangement • predefined effects, • effects modification, • Operation modes : <ul style="list-style-type: none"> - 1 x RGB (color) - 1 x RGBW (color + white - brightness control) - 1 x RGBWW / RGB CCT (color + white - brightness and color temperature control) - 1 x RGB (color) + 1 x MONO (single color) - 1 x CCT (white - brightness and color temperature control) - 2 x CCT (white - brightness and color temperature control) - 1 x RGB (color) + 1 x CCT (white - brightness and color temperature control) - 5 x MONO (single color) / halogen bulb • µWiFi technology support 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • sunrise and sunset mode, • timer, • remote access, • voice control, • The ability to set the default status of the device after a power failure, • Energy consumption metering, • Power measurement, • Charts and measurement history • µWiFi technology support • Illuminated, color front panel with an additional control button
Housing	Plastic	Plastic (ABS), DIN, TS-35 rail mounting
"Index of Protection"	IP20	IP20
Color	Black	White
Operation temp	-20 °C ... 50 °C	-20 °C ... 50 °C
Weight	0.026 kg	0.07 kg
Dimensions	43 x 35 x 18 mm	90 x 17.5 x 65 mm
Manufacturer / Brand	BleBox	BleBox
Guarantee	2 years	2 years