



	<a href="#">STRAIGHT SOCKET LE-50112 230 V 16 A LEGRAND</a>	<a href="#">ACCESS CONTROLLER MC16-PAC-ST-2-KIT ROGER</a>
		
	25.03 EUR 25.03 EUR	524.92 EUR 524.92 EUR
Rated voltage	230 V / 50 Hz	...
Number of served transitions	...	2 (two-way)
Maximal current load	16 A	...
Number of supported readers	...	8
Grounding	✓	...
Electrical cable	max. 3 x 2.5 mm <sup>2</sup>	...
Number of users	...	unlimited (purchase of the appropriate license required)
Cable terminals	automatic spring terminals	...
Socket type	CEE 7/5	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Buffer memory	...	8 000 000 events buffer
"Index of Protection"	IP44	...
Number of access zones	...	4
IK rating	IK08	...
Number of alarm zones	...	4
Color	Black	...
Battery backup support	...	12 V / 20 Ah
Communication	...	<ul style="list-style-type: none"> <li>• Ethernet - RJ-45 socket</li> <li>• RACS 5 v2 (Roger)</li> <li>• RS-485 interface</li> </ul>

Main features	...	<ul style="list-style-type: none"> <li>• Metal housing</li> <li>• The MCX2D I/O expander included</li> <li>• Integrated support in VISO ST software</li> <li>• Functions in the VISO ST system: <ul style="list-style-type: none"> <li>- MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system : 128</li> </ul> </li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• 17 ... 22 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>
Operation temp	...	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)
Weight	0.084 kg	4.25 kg
Dimensions	Ø 56 x 115 mm	405 x 365 x 123 mm
Manufacturer / Brand	LEGRAND	ROGER
Guarantee	2 years	3 years