

	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTL-AI80FORTD 4.5 mm - 1080p	RFID PROXIMITY CARD ATLO-308 13.56 MHz UL	TV OR MONITOR MOUNT BRATECK-LCD-501N	POWER DISTRIBUTION UNIT ACAR-XPROTECTOR	CEE-PLUG PCE-0256 400 V 32 A 5P 6H IP44 / IP54
					
	43.66 EUR 43.66 EUR	1.40 EUR 1.40 EUR	3.58 EUR 3.58 EUR	20.38 EUR 20.38 EUR	5.83 EUR 5.83 EUR
Standard	...	13.56 MHz UL
Rated voltage	230 V AC / 50 Hz	400 V / 50 ... 60 Hz
Compatibility	...	ISO/IEC 14443A
Total maximal current	10 A	...
Maximal current load	32 A
Possibility of programming the serial number (ID)	...	—
Mounting standard	VESA 75, 100
Screen size range	max. 32 "
Maximal total load	2300 W	...
Scanning system	Progressive
Number of poles	5P
Ability to write to internal memory	...	192 B
Bearing capacity	30 kg
Response time	< 25 ns	...
Grounding	6h
Serial Number overprint	...	—
Distance from mounting surface	88 mm from wall
Number of outlets	5 grounded outlets 10A/250V	...
Electrical cable	max. 5 x 6 mm ²
Optical zoom	—
Cable terminals	screw terminals
Plug type	CEE
Tilt adjustment	-15 ° ... 15 °
Main features	...	Range : ~ 10 cm ,
Horizontal rotation	-24 ° ... 24 °
Sensor	1/2.9 " GC2093 1/2.9 " GC2053
Contact material	CuZn
Rotation in the plane of the screen	—
Matrix size	2.1 Mpx 2 Mpx
Automatic delayed fuse	10 A / 250 V	...
Maximum wire insulation diameter	22 mm
Lens	4.5 mm 4.5 mm
Leak current	< 0.5 mA	...
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Cards support	13.56 MHz S50
Nominal stroke current	1 kA (L/N) - (8/20μs)	...
Keyboard built-in	—
Doorbell button	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Switch	two-way, with light indication	...
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p 640 x 480 px
View angle	66 ° 66 ° 90 °
Maximum stroke current	4.5 kA (L/N) - (8/20µs)	...
Interface	USB, RS-232 TTL
Length of the cable	1.45 m	...
Maximum background illumination	100 000 Lux
QR codes reading	<ul style="list-style-type: none"> • 1D : EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codabar, Interleaved 2 of 5 (ITF), ITF-6, ITF-14, ISBN, ISSN, MSI-Plessey, GS1 Databar, Code 11, Industrial 25, Standard 25, Plessey, Matrix 2 of 5 • 2D : QR Code, Data Matrix, PDF417, Aztec
Reading distance	<ul style="list-style-type: none"> • EAN13 (13 mm) : 30 ... 140 mm • Code 39 (5 mm) : 30 ... 50 mm • QR Code (20 mm) : 35 ... 120 mm • Data Matrix (10 mm) : 30 ... 70 mm • PDF417 (6.67 mm) : 30 ... 80 mm
Minimal contrast	25 %
Standard	TCP/IP
Range of IR illumination	5 m
White light LED illuminator range	5 m
Temperature measurement	✓
Temperature measurement range	35.7 °C ... 42 °C
Accuracy of temperature measurement	± 0.3 °C
Temperature measurement distance	0.7 m ... 1.2 m
Face recognition distance	0.5 m ... 2.0 m (max 30 000 faces in the database)
Internal memory	Support storage of 50 000 records
Video output	—
RS-485 interface	✓
Wiegand interface	✓
Memory card slot	—
Alarm inputs / outputs	0 / 1
Audio	Speaker built-in
Network interface	10/100 Base-T (RJ-45)
Network protocols	IPv4, TCP/IP, HTTP, MQTT, RTSP, SMTP, NTP
WEB Server	Built-in
ONVIF	—
Default IP address	DHCP / 192.168.1.88



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	admin / 12345
Web browser access ports	80
PC client access ports	80
Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera and the result of temperature measurement - 800 x 1280 px, 8 " • Wiegand 34/26 • Day/Night mode (color/b&w/auto) • RESET button • Alarm output of NO/NC relay type • Relay output operating modes: access control or notification of an exception • Built-in QR code reader
Power supply	12 V / 2 A DC
Power consumption	≤ 18 W
Housing	Compact - Metal	Plastic - non-flammable	...
Color	Silver	...	Black	...	Red
"Index of Protection"	—	IP44 / IP54
Operation temp	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)
Weight	1.8 kg	0.005 kg	0.524 kg	0.51 kg	0.23 kg
Dimensions	366 x 132 x 144 mm	86 x 54 x 0.8 mm	115 x 115 x 88 mm	365 x 65 x 52 mm	155 x 85 x 73 mm
Montage hole diameter	35 mm
Length of the cable	65 cm
Supported languages	English, French, Spanish, Ukrainian, Italian
Manufacturer / Brand	APTI	ATLO	BRATECK	...	PCE
Guarantee	3 years	2 years	2 years	2 years	2 years