



| | | |
|---|--|--|
| | RFID PROXIMITY CARD ATLO-D194 | ACCESS POINT 4G LTE +ROUTER ARCHER-MR400 2.4 GHz, 5 GHz 867 Mbps + 300 Mbps TP-LINK |
| |  |  |
| | 0.64 EUR 0.64 EUR | 124.59 EUR 124.59 EUR |
| Standard | <ul style="list-style-type: none"> • 13.56 MHz S50, • Unique EM 125kHz | ... |
| Frequency range | ... | 2.4 GHz , 5 GHz |
| Compatibility | ISO/IEC 14443A | ... |
| Possibility of programming the serial number (ID) | — | ... |
| Ability to write to internal memory | — | ... |
| Serial Number overprint | — | ... |
| Antenna type | ... | 3 x WiFi - built-in , 2 x 4G LTE |
| Standards | ... | IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3/3u |
| Baud rates | ... | <ul style="list-style-type: none"> • 5 GHz : 867 Mbps (max) + 2.4 GHz : 300 Mbps (max) • LTE : 150 Mbps |
| Modulation type | ... | DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM |
| LAN ports | ... | <ul style="list-style-type: none"> • 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN |
| Receiver sensitivity | ... | 5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -67dBm • 11ac HT40: -64dBm • 11ac HT80: -60dBm • 11n HT20: -71dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -76dBm • 11n HT20: -73dBm • 11n HT40: -67dBm |
| LTE | ... | ✓ |
| QSS | ... | ✓ |
| WDS | ... | ✓ |

| | | |
|-------------------------------|-------------------|--|
| Number of LAN ports | ... | 4 x 10/100 Mbps |
| Power supply | ... | 12 V DC / 1 A (power adapter included) |
| Operation temp | ... | 0 °C ... 40 °C |
| Permissible relative humidity | ... | 95 % (non-condensing) |
| Main features | Range : ~ 10 cm , | <ul style="list-style-type: none"> • SIM socket • WPS/RESET button |
| Weight | 0.005 kg | 0.26 kg |
| Dimensions | 86 x 54 x 0.8 mm | 202 x 163 x 34 mm |
| Manufacturer / Brand | ATLO | TP-LINK |
| Guarantee | 2 years | 3 years |