





	CABLES TESTER CS-NT24	FLUSH BOX 6-GANG M-6X60-FP SIMET	TWILIGHT SENSOR MCE-35	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA HAC-HDBW1500E-0280B-S2 - 5 Mpx 2.8 mm DAHUA
				
	3304.56 CZK 3304.56 CZK	137.30 CZK 137.30 CZK	241.92 CZK 241.92 CZK	2441.43 CZK 2441.43 CZK
Number of sections	...	6
Maximal load	15 A / 3450 W	...
Standard	AHD / HD-CVI / HD-TVI / CVBS
Sensor	1/2.7 " Progressive Scan CMOS
Tested cables	STP / UTP cat. 5, 5e, 6, 6e - RJ45 (8P8C), RJ11 (6P4C), Coaxial cable
Lighting switching threshold	< 2 Lux ... 100 Lux	...
Matrix size	5 Mpx
Material	...	Plastic
Operation temp	-20 °C ... 40 °C	...
Typical battery charge time	3 h
Backup time	16 h
Resolution	2880 x 1620 - 5 Mpx @ HD-CVI : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 960 x 576 - 960H, PAL
Range of IR illumination	30 m
IR illuminator power adjustment	Automatic
Lens	2.8 mm, F1.85
View angle	• 98 ° (manufacturer data) • 103 ° @ HD-CVI / 90 ° @ AHD / HD-TVI (our tests result)
IR illuminator support	ICR - Movable InfraRed filter

Main features	<ul style="list-style-type: none"> • 2.4 " LCD display - 320 x 240 px • Cable test and cable tracer : cable type, UTP cable's sequence and type test, the fault of RJ45 connector • Test TDR - RJ45 : pair status, length, attenuation, reflectivity, impedance, skew - Length of the cable max. 180 m • Detection of the connected port in switch • Test PING : correct operation of the IP camera's Ethernet port, correct IP address • IP Scan • Identification of the network port and duplex mode • Identification the wire in the group of wires • Telephone line condition detection • Automatic power-off : 10 ... 120 minutes 	<ul style="list-style-type: none"> • Flush-mounted • 10 fixing points • Cover mounting with screws • 4 Mounting screws - included
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/night mode • Auto White Balance • Privacy zones
OSD menu	OSD menu available via recorder
Power supply	Cables tester : Li-Ion battery 3.7 V / 2000 mAh, USB DC 5V/2A power adapter (included) Probe : 2 x 1.5V, type AA/LR6/FR6 battery (not included)	...	220 ... 240 V AC	12 V DC / 330 mA
Power consumption	≤ 4.2 W
Housing	Plastic	Dome, Metal
Color	...	Orange / White	...	White
"Index of Protection"	...	IP20	IP65	IP67
Vandal-proof	IK10

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp	-40 °C ... 60 °C
Weight	0.28 kg - Cables tester 0.11 kg - Probe	0.190 kg	0.098 kg	0.33 kg
Dimensions	175 x 88 x 40 mm - Cables tester 220 x 47 x 32 mm - Probe	212 x 156 x 50 mm (flush mounting box) 230 x 170 x 2 mm (cover)	<ul style="list-style-type: none"> • 48 x 63 x 27 mm • 42 x 71 x 29 mm 	Ø 110 x 81 mm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Italian
Manufacturer / Brand	...	SIMET	...	DAHUA
Guarantee	2 years	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00