



	IP CAMERA DS-2CD2T87G2P-LSU/SL(4MM)(C)/BLACK PANORAMIC ColorVu - 7.4 Mpx 2 x 4 mm Hikvision	ACCESS CONTROLLER MC16-PAC-ST-1-KIT ROGER
		
	724.28 EUR 724.28 EUR	349.75 EUR 349.75 EUR
Standard	TCP/IP	...
Number of served transitions	...	1 (two-way)
Number of supported readers	...	4
Sensor	2 x 1/1.8 " Progressive Scan CMOS	...
Number of users	...	unlimited (purchase of the appropriate license required)
Matrix size	2 x 3.7 Mpx - 8 Mpx (total)	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Scanning system	Progressive	...
Buffer memory	...	8 000 000 events buffer
Number of access zones	...	4
Resolution	5120 x 1440 - 7.4 Mpx	...
Number of alarm zones	...	4
Battery backup support	...	12 V / 20 Ah
Lens	2 x 4 mm	...
View angle	180 ° (horizontal) 44 ° (vertical)	...
Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface
White light LED illuminator range	40 m	...
RS-485 interface	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...

Main features	...	<ul style="list-style-type: none"> • Metal housing • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128
Audio	<ul style="list-style-type: none"> • Microphone built-in • External microphone input • Audio output • Bi-directional audio streaming support • Digital Noise Reduction 	...
Main stream frame rate	20 fps @ 7.4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Operation temp	...	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.64	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization 	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...

Main features	<ul style="list-style-type: none"> • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • NAS - Network Attached Storage support • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Active deterrence function - Light and sound alarm • White light (LED) illuminator built-in : 4 LEDs • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Configurable: brightness, contrast, saturation • Smart motion detection (with recognizing people and vehicles) • Intelligent image analysis - crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, scene changing 	...
Power supply	<ul style="list-style-type: none"> • 12 V DC / 790 mA, • PoE (802.3af) 	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Power consumption	<ul style="list-style-type: none"> • ≤ 9.5 W @ 12 V DC • ≤ 10.5 W @ PoE 	...
Housing	Compact, Metal	...
Color	Black	...
Vandal-proof	—	...
"Index of Protection"	IP67	...
Operation temp	-30 °C ... 60 °C	...
Weight	1.45 kg	3.9 kg
Dimensions	119 x 105 x 305 mm	405 x 365 x 120 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
SAP Code	311323807	...
Manufacturer / Brand	Hikvision	ROGER
Guarantee	3 years	3 years