



	IP CAMERA APTI-RF42MAP-37 Wi-Fi, PINHOLE - 4 Mpx 3.7 mm	FLASH DRIVE USB-U106-20-16GB 16 GB USB 2.0 DAHUA
		
	76.34 EUR 76.34 EUR	3.31 EUR 3.31 EUR
Standard	TCP/IP	...
Capacity	...	16 GB
Sensor	1/3 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Connector type	...	USB 2.0 - USB-A
Write transfer rate	...	3 ... 10 MB/s
Read speed	...	10 ... 25 MB/s
Main features	...	Light and durable construction
Resolution	2688 x 1512 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	3.7 mm (pinhole)	...
View angle	• 70 ° (manufacturer data) • 90 ° (our tests result)	...
S/N ratio	> 52 dB	...
Min. illumination	0.01 Lux @ F1.6 (AGC off)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / -	...
Main stream frame rate	25 fps - 4 Mpx	...
Network interface	• 10/100 Base-T (RJ-45) • Wi-Fi - IEEE 802.11 b/g/n	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP	...
Audio	• Audio input - Jack 3.5 mm socket • Audio output - Jack 3.5 mm socket • Bi-directional audio streaming support	...
ONVIF	2.4	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...

Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin	...
Web browser access ports	80	...
PC client access ports	80	...
WEB Server	Built-in Built-in	...
Mobile client access ports	80	...
Max. number of on-line users	10 10	...
Port ONVIF	80	...
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area) • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • F-DNR (Defog) - Reduction of image noise caused by precipitation • Possibility to change the resolution, quality and bit rate • Motion Detection • Privacy zones • Configurable: brightness, contrast, saturation • Mirror - Mirror image • Sharpness - sharper image outlines • Intelligent image analysis : intrusion 	...
Power supply	12 V DC / 190 mA	...
Power consumption	≤ 2.3 W	...

Housing	Mini - Metal	...
Color	Black	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.14 kg	...
Dimensions	37.5 x 37.5 x 30 mm	40 x 12 x 5 mm
Supported languages	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	APTI	DAHUA
Guarantee	2 years	5 years