





	CONNECTOR FOR SOLAR INSTALLATIONS MC4/ZAC*P5	SPEAKER CABLE HI-FI/2X0.35	RFID PROXIMITY CARD WITH MODIFIED UID ATLO-115	EXTENDER HDMI+USB-EX-100-4K-V2
				
	3.46 GBP 3.46 GBP	0.18 GBP 0.18 GBP	1.82 GBP 1.82 GBP	210.43 GBP 210.43 GBP
Standard	Unique EM 125kHz	...
Compatibility	EM4100/4102	...
Possibility of programming the serial number (ID)	✓	...
In section	...	100 m . Price for 1m when buying a whole roll
Ability to write to internal memory	330 bit	...
In package	5 pcs The price for package
Serial Number overprint	—	...
Connector type	MC4 - set (M + F) / Crimping
Inner conductor	...	2 x Ø 0.35 mm Cu-OFC Stranded wire
Rated voltage	1000 V
Supported HDMI resolutions	480p, 576i, 576p, 720p, 1080i, 1080p, 4K x 2K, 4K UHD
Outer coating	...	PVC
Rated current	30 A
Coating color	...	Colorless
Material	Plastic + Metal
Maximal transmission range	100 m UTP cat. 5e, 6 @ 4K UHD ,
Color	Black
Max. number of receivers working in the same time	253
Protocols	HDbitT
Application	Solar installations - For cables 2.5mm ² , 4mm ² , 6mm ²
"Index of Protection"	IP67
Main features	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • Audio transmission via network
Flammability class	UL94-VO

Main features	<ul style="list-style-type: none"> • Range : ~ 10 cm, • The T5577 chip, • The ability to save and modify additional information 	<ul style="list-style-type: none"> • The devices do not require direct connection, they also operate via the LAN network • The need for a separate power supply for the transmitter and receiver
Manufacturer / Brand	ATLO	...
Power supply	<ul style="list-style-type: none"> • Transmitter 5 V DC / 1 A (power adapter included) • Receiver 5 V / 1 A (power adapter included)
Operation temp	-20 °C ... 60 °C
Permissible relative humidity	0 % ... 90 % (non-condensing)
Weight	0.022 kg	...	0.01 kg	0.31 kg
Dimensions	Ø 19 x 87 mm	...	86 x 54 x 2 mm	133 x 90 x 26 mm - Transmitter or receiver dimensions
Guarantee	2 years	2 years	2 years	2 years