


	<a href="#">PROJECTOR MOUNT PD-670</a>	<a href="#">UPS AT-UPS650-LED 650 VA EAST</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-S8-DUAL</a>
			
	167.94 NOK 167.94 NOK	664.87 NOK 664.87 NOK	268.65 NOK 268.65 NOK
Nominal power	...	390 W	...
Bearing capacity	20 kg	...	...
Rated voltage	...	...	230 V AC / 50 Hz
Apparent Power	...	650 VA	...
Nominal load current	...	...	10 A (total)
Input voltage	...	165 V ... 275 V AC	...
Nominal voltage of surge suppressor	...	...	250 V / 50 Hz
Protection level of surge suppressor	...	...	≤ 1.3 kV (L/N)
Distance from mounting surface	• 430 ... 650 mm (vertical), • 350 ... 560 mm (horizontal)	...	...
Input frequency	...	50 / 60 Hz (auto detection)	...
Number of outlets	...	...	8 grounded outlets 10A/250V
Automatic delayed fuse	...	...	✓
Projector mounting holes distances	Ø 225 ... 316 mm	...	...
Output voltage	...	230 V AC ± 10 % (Approximated Sine Wave)	...
Nominal stroke current	...	...	2 kA (L/N) - 8/20 µs
Tilt adjustment	-15 ° ... 15 °	...	...
Output frequency	...	50 / 60 Hz ± 1 %	...
Maximum stroke current	...	...	6.5 kA (L/N) - 8/20 µs
Horizontal rotation	-8 ° ... 8 °	...	...
Transfer time	...	≤ 10 ms	...
Charging time (recover to 90% capacity)	...	8 hours	...
Response time	...	...	< 25 ns
Color	Silver	...	...
Material	Steel - powder painted	...	...
Battery	...	1 pcs - 12V/7Ah	...
Switch	...	...	two-way, with light indication
Length of the cable	...	...	1.4 m
Housing	...	...	Plastic - non-flammable

Estimated battery operation time	...	<ul style="list-style-type: none"> <li>• 16 minutes @ 100 W</li> <li>• 7 minutes @ 200 W</li> <li>• 4 minutes @ 300 W</li> </ul>	...
Number of outputs	...	2 pcs CEE 7/3 (Schuko)	...
Protections	...	<ul style="list-style-type: none"> <li>• Fuse</li> <li>• Overvoltage</li> <li>• Overload protection</li> <li>• Overcharge protection</li> <li>• Telephone line filter</li> </ul>	...
Operation state indication	...	<ul style="list-style-type: none"> <li>• LED diodes,</li> <li>• Sound signaling</li> </ul>	...
Main features	Possibility to mount on the wall or ceiling	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Compatible with power generators</li> <li>• Remote management - UPSmart application included</li> <li>• Built-in EMI, RFI filter</li> <li>• Configurable alarm</li> </ul>	...
Application	...	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>	...
Housing type	...	Tower	...
Operation temp. / Relative humidity	...	0 °C ... 40 °C / 20 ... 90 %	...
Weight	1.5 kg	5.36 kg	0.52 kg
Dimensions	...	330 x 163 x 95 mm	445 x 54 x 55 mm
Manufacturer / Brand	...	EAST	...
Guarantee	2 years	2 years	2 years