



	MOUNTING PROFILE USP-SM-1100 FOR SOLAR PANELS	ACCESS CONTROLLER ASC2102B-T DAHUA
		
	13.85 EUR 13.85 EUR	174.28 EUR 174.28 EUR
Material	Aluminum	...
Number of served transitions	...	2 (two-way)
Support	...	DAHUA ASC2204C-H
Number of supported readers	...	4 pcs
Battery backup support	...	—
Output lines	...	5 pcs - Relay
Alarm inputs / outputs	...	5 / 1
Communication	...	<ul style="list-style-type: none"> • RS-485, • Wiegand 34/26, • Control panel CAN (Controller Area Network)
Power supply	...	12 V DC / 1 A
Main features	...	<ul style="list-style-type: none"> • 20 000 indexed users • History of 30 000 events • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Door Left Open and Door Forced Open alarms • Watchdog built-in • Possibility to mount on a wall, or on the DIN TS-35 rail
Operation temp	...	-30 °C ... 60 °C
Permissible relative humidity	...	max. 95 % (non-condensing)
Weight	0.21 kg	0.384 kg
Dimensions	1100 x 50 x 50 mm	209 x 117 x 51 mm
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years