



| | WIRELESS VIDEO DOORBELL ATLO-DBC2-TUYA Wi-Fi, Tuya Smart | EXTENDER HDMI+USB-EX-100-4K |
|-------------------------------|--|--|
| |  |  |
| | 17672.12 HUF 17672.12 HUF | 81384.62 HUF 81384.62 HUF |
| Sensor | Progressive Scan CMOS - 2 Mpx | ... |
| Resolution | 1920 x 1080 px - 1080p | ... |
| Lens | 2.5 mm | ... |
| View angle | 135 ° | ... |
| Supported HDMI resolutions | ... | 480p, 576i, 576p, 720p, 1080i, 1080p, 4K x 2K, 4K UHD |
| IR illuminator | 10 m | ... |
| LED illuminator | — | ... |
| Wireless transmission range | The range limited only by the availability of the Wi-Fi network | ... |
| Wi-Fi standard | 2.4 GHz IEEE 802.11 b/g/n | ... |
| Network interface | 2.4 GHz Wi-Fi | ... |
| Mobile phones support | The Tuya Smart free application on Android The Tuya Smart free application on iOS | ... |
| Maximal transmission range | ... | <ul style="list-style-type: none"> • 70 m UTP cat. 6 @ 4K UHD, • 70 m UTP cat. 5, 5e @ 1080p • 50 m UTP cat. 5e @ 4K UHD (our tests result) |
| Image compression method | H.264 / JPEG | ... |
| Main features | ... | <ul style="list-style-type: none"> • Very good image quality with no visible distortions caused by compression • No delays in video transmission • No delays in mouse control operations • Transition of the HDMI signal in the transmitter • S/PDIF output |
| Operation temp | ... | -20 °C ... 60 °C |
| Permissible relative humidity | ... | 0 % ... 90 % (non-condensing) |

| | | |
|-----------------------|---|--|
| Main features | <ul style="list-style-type: none"> • Micro SD memory cards up to 128GB support (possible local recording), • Motion Detection - PIR detector - Detector range 5 m, • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging • Low current consumption • Operating frequency - Wireless doorbell : 433 MHz | <ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse |
| Mount | Surface-mounted | ... |
| Power supply | <ul style="list-style-type: none"> • 3 x 18650 battery 3.7 V / 2600 mAh (not included) • 5 V DC - Charging via micro USB port (cable included) | <ul style="list-style-type: none"> • Transmitter 5 V DC / 2 A (power adapter included) • Receiver 5 V / 2 A (power adapter included) |
| Housing | Plastic | ... |
| Color | White / Black | ... |
| "Index of Protection" | IP44 | ... |
| Weight | <ul style="list-style-type: none"> • 0.14 kg - Wireless Video Doorbell • 0.06 kg - cover | 0.29 kg |
| Dimensions | <ul style="list-style-type: none"> • 150 x 75 x 36 mm - Wireless Video Doorbell • 162 x 82 x 47 mm - cover | 150 x 107 x 28 mm - Transmitter or receiver dimensions |
| Guarantee | 2 years | 2 years |