



	MULTI-SOCKET PLUG LE-50637 3680 W LEGRAND	SWITCH POE GTX-A1-06-42 4-PORT
		
	13.80 GBP 13.80 GBP	31.04 GBP 31.04 GBP
Rated voltage	230 V / 50 Hz	...
Maximal total load	3680 W	...
Total maximal current	16 A	...
Number of outlets	2 pcs 2P+Z	...
Grounding	✓	...
Housing	Plastic	...
LAN ports	...	<ul style="list-style-type: none"> • 4 x RJ45 (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
Color	White / Gray	...
Manufacturer / Brand	LEGRAND	...
Management	...	—
LED diodes	...	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act
Transmission speed	...	10 / 100 Mbps : 2 x Port LAN - Uplink + 4 x Port LAN & PoE
Operation modes	...	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 4 ports are isolated from each other and separately work with the 5, 6 ports • S - Extend - Range : 250 m @ 10 Mbps
Maximal output power	...	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 4 ports
Maximal total power	...	65 W
MAC addresses table	...	1k

Main features	...	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h
Certificates	...	CE, FCC Class B
Protections	...	Overvoltage \pm 3 kV
Power supply	...	100 ... 265 V AC
Operation temp	...	-10 °C ... 55 °C
Weight	0.15 kg	0.6 kg
Dimensions	110 x 61 x 101 mm	190 x 130 x 35 mm
Guarantee	2 years	2 years