



	CABLE TIE HOLDER PS-5-28X28/B*P100	IP SPEED DOME CAMERA OUTDOOR DS-2DE2A204IW- DE3(C0)(S6)(C) - 1080p 2.8 ... 12 mm Hikvision
		
	11.03 EUR 11.03 EUR	320.56 EUR 320.56 EUR
Standard	...	TCP/IP
Sensor	...	1/2.8 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx
In package	100 pcs The price for package	...
Holes dimensions	5 x 2 mm	...
Montage hole diameter	Ø 6 mm	...
Assembly	<ul style="list-style-type: none"> • The bottom layer is equipped with a Scotch tape, • Mounting with screws 	...
Resolution	...	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Scanning system	...	Progressive
Lens	...	2.8 ... 12 mm
View angle	...	101 ° ... 33 ° (manufacturer data)
Optical zoom	...	x 4
Digital zoom	...	x 16
Range of IR illumination	...	20 m
Video output	...	—
Preset rotation speed	...	<ul style="list-style-type: none"> • 100 °/s (horizontal) • 100 °/s (vertical)
Rotation speed (manual control)	...	0.1 °/s ... 100 °/s (horizontal) 0.1 °/s ... 100 °/s (vertical)
Horizontal rotation range	...	355 ° - Rotation of the head is limited by stops
Vertical rotation range	...	0 ° ... 90 °
RS-485 interface	...	—
Number of presets	...	300
Horizontal scan	...	—
Route settings	...	—
Image compression method	...	H.265+ H.265 / H.264+ / H.264 / MJPEG
Bitrate	...	32 ... 16384 kbps
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	...	25 fps @ 1080p

Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, HTTPS, IEEE 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour, WebSocket, WebSockets
WEB Server	...	Built-in, NVR compliance
Max. number of on-line users	...	20
ONVIF	...	✓
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	• Main stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • EIS - Electronic Image Stabilization • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • NAS - Network Attached Storage support • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Mirror - Mirror image • Motion Detection • Configurable Privacy Zones - 24 • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), abandoned/missing object, detection of entry into the area / exit from the area, face detection

Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 770 mA
Power consumption	...	≤ 9.2 W
Housing	...	Speed Dome, Metal
Color	Black	White + Black
Operation temp	...	-20 °C ... 60 °C
"Index of Protection"	...	IP66
Vandal-proof	...	IK10
Weight	...	0.62 kg
Dimensions	28 x 28 x 7 mm	Ø 131 x 102 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Manufacturer / Brand	...	Hikvision
SAP Code	...	327000658
Guarantee	2 years	3 years

